

SuperServer 1019GP-TT

1U Single Processor (Intel) 2 GPU System



Integrated Board



X11SPG-TF

Views: | [Angled View](#) | [Top View](#) |
| [Front View](#) | [Rear View](#) |

▶ [Drivers & Utilities](#) ▶ [BIOS](#) ▶ [IPMI](#) ▶ [Tested Memory](#) ▶ [Drive Options](#) ▶ [Tested M.2 List](#) ▶ [Manuals](#) ▶ [OS Certification Matrix](#)
▶ [Compatible GPU List](#)

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Key Applications

- Edge Computing
- Micro Data Center
- AI/ML, Deep Learning Training and Inference
- Virtualization
- Cloud Computing

Key Features

1. Supports up to 2 Active/Passive Cooling NVIDIA® GPUs in 1U
2. Single Socket P (LGA 3647) supports 2nd Gen Intel® Xeon® Scalable processor (Cascade Lake/Skylake)‡
3. 6 DIMMs; up to 1.5TB 3DS ECC DDR4-2933MHz† RDIMM/LRDIMM, Supports Intel® Optane™ DCPMM††
4. 2 PCI-E 3.0 x16 slots (support double-width GPU), 1 PCI-E 3.0 x16 low-profile slot (center right)
5. 6 Hot-swap 2.5" SAS/SATA drive bays
6. 2x 10GBase-T LAN ports via Intel X550
7. 2 M.2 form factor 2280, supports both M.2 NVMe and SATA SSD
8. 8 Heavy duty 4cm counter-rotating 4cm fans with air shroud & optimal fan speed control
9. 1400W High-efficiency Power Supply **Platinum Level (94%+)**

Specifications

Product SKUs

SYS-1019GP-TT ■ SuperServer 1019GP-TT

Motherboard

Super X11SPG-TF

Processor/Cache

CPU ■ Single Socket P (LGA 3647)
 ■ 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors[‡]
 ■ Support CPU TDP 70-205W

Cores ■ Up to 28 Cores

Note [‡] BIOS version 3.2 or above is required to support 2nd Gen Intel® Xeon® Scalable processors (codenamed Cascade Lake-R)

GPU

Supported GPUs ■ 2 Double-Width/Single-Width PCI-E 3.0 x16 Card (Full Height Full Length)
 ■ NVIDIA V100, M10, P40, T4, Quadro RTX
 ■ Supports both active and passive cooled GPUs
 ■ [Compatible GPU list](#)

CPU-GPU Interconnect ■ PCI-E Gen 3 x16 Switch CPU-GPU Interconnect

System Memory

Memory Capacity ■ 6 DIMM slots
 ■ Up to 1.5TB 3DS ECC DDR4-2933MHz[†] RDIMM/LRDIMM
 ■ Supports Intel® Optane™ DCPMM^{††}

Memory Type ■ 2933[†]/2666/2400/2133MHz ECC DDR4 RDIMM/LRDIMM

Note [†] 2933MHz in two DIMMs per channel can be achieved by using memory purchased from Supermicro
^{††} Cascade Lake only. Contact your Supermicro sales rep for more info.

On-Board Devices

Chipset ■ Intel® C621 chipset

SATA ■ SATA3 (6Gbps) with RAID 0, 1, 5, 10

Network Connectivity ■ Intel® X550 Dual Port 10GBase-T
 ■ Virtual Machine Device Queues reduce I/O overhead
 ■ Supports 10GBASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output

IPMI ■ Support for Intelligent Platform Management Interface v.2.0
 ■ IPMI 2.0 with virtual media over LAN and KVM-over-LAN support

Graphics ■ ASPEED AST2500

Input / Output

Chassis

Form Factor ■ 1U Rackmount

Model ■ **CSE-118GTS-1K43BP2**

Dimensions

Height ■ 1.7" (43mm)

Width ■ 17.2" (437mm)

Depth ■ 28.5" (724mm)

Weight ■ Net Weight: 28 lbs (12.70 kg)
 ■ Gross Weight: 36 lbs (16.33 kg)

Available Color ■ Black

Front Panel

Buttons ■ Power On/Off button
 ■ System Reset button

LEDs ■ Power LED
 ■ Hard drive activity LED
 ■ Network activity LEDs
 ■ System Overheat LED / Fan fail LED

Expansion Slots

PCI-Express ■ 2 PCI-E 3.0 x16 (FHFL) slots - supporting up to 2 GPUs
 ■ 1 PCI-E 3.0 x16 slot (left riser)

Drive Bays / Storage

Hot-swap ■ 6 Hot-swap 2.5" SAS/SATA drive bays

M.2 ■ Supports 2 M.2 form factor 2280
 ■ Supports both M.2 NVMe and SATA SSD

System Cooling

Fans ■ 8 heavy duty counter-rotating 4cm fans with air shroud and optimal fan speed control

Power Supply

1400W High-efficiency AC power supply with Digital Switching Control & PMBus 1.2

AC Voltage ■ 1200W: 100-140 V, 14.7-10.5A, 50-60 Hz
 ■ 1400W: 180-240 V, 10.5-8.0A, 50-60 Hz

+5V standby ■ 6 Amp

+12V ■ 100 Amp/115 Vac
 ■ 117 Amp/230 Vac

With Power Distributor ■ +5V: 14 Amp

Certification



Platinum Certified

SATA	<ul style="list-style-type: none"> 6 SATA3 (6Gbps) ports
LAN	<ul style="list-style-type: none"> 2 RJ45 10GBase-T ports 1 RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 2 USB 3.0 ports (rear) 2 USB 2.0 ports (rear)
Video	<ul style="list-style-type: none"> 1 VGA port
Serial Port	<ul style="list-style-type: none"> 1 COM Port header
DOM	<ul style="list-style-type: none"> 2 DOM (Disk on Module) power connectors

System BIOS

BIOS Type	<ul style="list-style-type: none"> AMI 32Mb SPI Flash ROM
------------------	--

Management

Software	<ul style="list-style-type: none"> Intel® Node Manager <u>IPMI 2.0</u> KVM with dedicated LAN NMI <u>SPM, SUM</u> <u>SuperDoctor® 5</u> Watch Dog
Power Configurations	<ul style="list-style-type: none"> ACPI / APM Power Management

PC Health Monitoring

CPU	<ul style="list-style-type: none"> Monitors for CPU Cores, Chipset Voltages, Memory. 4+1 Phase-switching voltage regulator
FAN	<ul style="list-style-type: none"> Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors
Temperature	<ul style="list-style-type: none"> Monitoring for CPU and chassis environment Thermal Control for fan connectors

Operating Environment

RoHS	<ul style="list-style-type: none"> RoHS Compliant
Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11SPG-TF	1	Super X11SPG-TF Motherboard
	CSE-118GTS-1K43BP2	1	1U SC118G Chassis
Backplane	BPN-SAS-118TQ	1	6-port 1U TQ (W/ AMI 9072) backplane, support up to 6x 2.5-inch SAS/SATA HDD/SSD
Cable 1	CBL-0484L	4	SATA,INT,ROUND,ST-ST,55CM,30AWG
Cable 2	CBL-CDAT-0662	2	CBL,SGPIO,2X4F TO 2X4F,P2.54,ROUND CABLE,61.5CM,28AWG
Cable 3	CBL-PWEX-0663	1	PCIe 8 pin male(black) to CPU 8 pin female(white) power adapter, 5cm, 18AWG, 9A/pin, 0~80C, RoHS/REACH
Cable 4	CBL-PWEX-1028	1	Tesla family GPU,2x4F/CPU to 2x4F/CPU,P4.2, 30CM,16AWG, 10A/pin, -40~105C
Cable 5	CBL-SAST-0624	2	SATA,INT,ROUND,ST-ST,70CM,30AWG
Riser Card	RSC-R1U-E16R	1	RSC-R1U-E16R
Riser Card	RSC-R1UG-E16-UP	1	1U LHS Riser Card with one PCI-E x16 for UP GPU MBs
Riser Card	RSC-R1UG-E16R-UP	1	1U RHS Riser Card with 1 PCI-E x16 for UP GPU MB
Heatsink / Retention	SNK-P0067PS	1	1U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
Power Supply	PWS-1K43F-1R	1	1400W redundant digital power supply

Optional Parts List

	Part Number	Qty	Description
Other GPUs Cables	CBL-PWEX-1059	1	Quadro family GPU, 2x4F/RA/CPU to two (2x3F+2x1F)/PCIe,P4.2, 36CM,17/20AWG,8A/pin(17AWG), 6A/pin(20AWG), -25~80C, RoHS
AOC-S3008L-L8i (SAS3)	CBL-SAST-0699	2	Mini SAS HD-4 SATA, 12G
AOC-S3108L-H8iR-16DD (SAS3)	CBL-SAST-0699	2	Mini SAS HD-4 SATA, 12G
AOC-S3108L-H8iR (SAS3)	CBL-SAST-0699	2	Mini SAS HD-4 SATA, 12G
Super Cap for LSI 3108	BKT-BBU-BRACKET-05	1	Mounting Bracket for LSI BBUs
	BTR-TFM8G-LSICVM02	1	LSI Super Cap
Network Cards	AOC-S100G-m2C	-	Standard low-profile 2-port QSFP28 100GbE PCI-E 3.0 x16, based on Mellanox ConnectX-4 EN chipset
	AOC-MCX516A-CCAT	-	Mellanox MCX516A-CCAT PCIe 2-port 100GbE QSFP28 Gen3x16 CX-5 EN. RoHS
	AOC-S40G-i2Q	-	Standard Low-Profile Dual-port 40GbE controller with 2x QSFP ports
	AOC-MCX512A-ACAT	-	Mellanox MCX512A-ACAT PCIe 2-port 25GbE SFP28 Gen3x8 CX-5 EN. RoHS
	AOC-MCX4121A-ACAT	-	Mellanox MCX4121A-ACAT 25GbE dual-port SFP28, PCIe3.0 x8, tall bracket Lx EN, HF, RoHS
	AOC-S25G-b2S	-	Standard Low-Profile Dual-port 25GbE controller with 2 SFP28 ports, based on Broadcom BCM57414
	AOC-S25G-m2S	-	Standard low-profile 2-port 25GbE with SFP+, based on Mellanox ConnectX-4 LX EN chipset
	AOC-STG-b4S	-	Standard Low-profile Quad-port 10GbE controller with 4x SFP+ ports
	AOC-STG-i4S	-	Standard Low-Profile Quad-port 10GbE controller with 4x SFP+ ports
	AOC-STGN-i2S	-	Standard Low-Profile Dual-port 10GbE controller with 2x SFP+ ports
	AOC-STGN-i1S	-	Standard Low-Profile Single-port 10GbE controller with 1x SFP+ port

	AOC-STG-i2T	-	Standard Low-Profile Dual-port 10GbE controller with 2x RJ45 (10GBase-T) ports
	AOC-SGP-i4	-	Standard Low-Profile Quad-port GbE controller with 4x RJ45 ports
	AOC-SGP-i2	-	Standard Low-Profile Dual-port GbE controller with 2x RJ45 ports
GPUs Air Shroud Kit	MCP-310-81806-0B	-	Nvidia Fermi GPU Air shroud for 818G/118G
Global Services & Support	QS4HR3/2/1	-	3/2/1-year onsite 24x7x4 service
	QSNBD3/2/1	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC • eStore	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)