

# SuperServer 7048R-TRT



**Integrated Board**



**Super X10DRi-T**

**Available Colors:**

Black



[▶ Drivers & Utilities](#)
[▶ BIOS](#)
[▶ IPMI](#)
[▶ Tested Memory](#)
[▶ Manuals](#)  
[▶ OS Certification Matrix](#)
[▶ Quick-References Guide](#)
[▶ Drive Options](#)

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

## Key Features

**Cloud and Virtualization needs**  
**Compute Intensive Application**  
**Database Processing and Storage**  
**High Availability Storage**  
**Mission-critical Applications**

1. Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4<sup>†</sup>/ v3 family; QPI up to 9.6GT/s
2. Up to **2TB<sup>†</sup>** ECC 3DS LRDIMM , up to DDR4- **2400<sup>†</sup>**MHz ; 16x DIMM slots
3. 3 PCI-E 3.0 x16, 3 PCI-E 3.0 x8 slots
4. Intel® X540 Dual port 10GBase-T
5. Intel C612 controller for 8 SATA3 ports; RAID 0, 1, 5, 10
6. 8x 3.5" Hot-swap SATA3 HDD Bays
7. 920W Redundant Power Supplies **Platinum Level (94%)**

# Specifications

**Product SKUs - Discontinued SKU (EOL). Please contact sales-rep for alternative options.**

**SYS-7048R-TRT** ■ SuperServer 7048R-TRT (Black)

**Recommended Replacement** ■ [SYS-7049P-TRT](#)

## Motherboard

**Super X10DRi-T**

## Processor/Cache

**CPU** ■ Intel® Xeon® processor E5-2600 v4<sup>†</sup>/ v3 family (up to 145W TDP) \*  
■ Dual Socket R3 (LGA 2011)

**Cores / Cache** ■ Up to **22 Cores**<sup>†</sup> / Up to **55MB**<sup>†</sup> Cache

**System Bus** ■ QPI up to 9.6 GT/s

**Note** <sup>†</sup> BIOS version 2.0 or above is required

**Note** \* Please contact Supermicro Technical Support for additional information about frequency optimized CPUs and specialized system optimization.

## System Memory

**Memory Capacity** ■ 16x 288-pin DDR4 DIMM slots  
■ Up to 2TB<sup>†</sup> ECC 3DS LRDIMM, 512 ECC RDIMM

**Memory Type** ■ **2400**<sup>†</sup>/2133/1866/1600MHz ECC DDR4 SDRAM 72-bit

**DIMM Sizes** ■ RDIMM: 32GB, 16GB, 8GB, 4GB  
■ LRDIMM: 64GB, 32GB  
■ 3DS LRDIMM: 128GB

**Memory Voltage** ■ 1.2 V

**Error Detection** ■ Corrects single-bit errors

## On-Board Devices

**Chipset** ■ Intel® C612 chipset

**SATA** ■ SATA 3.0 (6Gbps) with RAID 0, 1, 5, 10

**IPMI** ■ Support for Intelligent Platform Management Interface v.2.0  
■ IPMI 2.0 with virtual media over LAN and KVM-over-LAN support  
■ ASPEED AST2400 BMC

**Network Controllers** ■ Intel® X540 Dual Port 10GBase-T  
■ Virtual Machine Device Queues reduce I/O overhead  
■ Supports 10GBASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output  
■ 1x Realtek RTL8201N PHY (dedicated IPMI)

**Video** ■ ASPEED AST2400 BMC

## Input / Output

**SATA** ■ 8x SATA3 (6Gbps) ports  
■ 2x SATA3 powered ports that support SATA DOM

## Chassis

**Form Factor** ■ 4U Rackmountable / Tower  
■ Optional Rackmount Kit

**Model** ■ **CSE-745TQ-R920B**

## Dimensions and Weight

**Height** ■ 17.2" (437mm)

**Width** ■ 7.0" (178mm)

**Depth** ■ 25.5" (648mm)

**Package** ■ 24" (H) x 14" (W) x 26.5" (D)

**Weight** ■ Net Weight: 56 lbs (25.6 kg)  
■ Gross Weight: 73.5 lbs (33.6 kg)

**Available Colors** ■ Black

## Front Panel

**Buttons** ■ Power On/Off button  
■ System Reset button

**LEDs** ■ Power LED  
■ Hard drive activity LED  
■ 2x Network activity LEDs  
■ System Overheat LED  
■ Power Fail LED

**Ports** ■ 2x USB Ports

## Expansion Slots

**PCI-Express** ■ 3x PCI-E 3.0 x16 (Full-height, Full-length)  
■ 3x PCI-E 3.0 x8 (Full-height, Full-length)

## Drive Bays

**Hot-swap** ■ 8x 3.5" Hot-swap SAS/SATA Drive Trays

**Peripheral Bay(s) [90° Rotatable]** ■ 2x 5.25" Peripheral Drive Bays  
■ 1x 5.25" Bay that fits 3.5" bay devices

## SAS / SATA Backplane

SAS / SATA Hard Drive Backplane w/AMI MG9072

## System Cooling

**Fans** ■ 3x 8cm hot-swap redundant PWM cooling fans  
■ 2x 8cm hot-swap exhaust Fans and air shroud

## Power Supply with Power Distributor

920W high-efficiency (94%+) AC-DC Redundant power supplies with PMBus and I2C

**AC Input** ■ 100-240 V, 50-60 Hz, 11-4.5 Amp

**DC Output** ■ 4 Amp @ +5V standby  
■ 75 Amp @ +12V

<b>LAN</b>	<ul style="list-style-type: none"> <li>2x RJ45 10GBase-T LAN ports</li> <li>1x RJ45 Dedicated IPMI LAN port</li> </ul>
<b>USB</b>	<ul style="list-style-type: none"> <li>Rear USB: 2x USB 3.0 + 2x USB 2.0</li> <li>Front USB: 2x USB 2.0</li> <li>USB Header: 2x 3.0, 2x 2.0, 1x Type A</li> </ul>
<b>Video</b>	<ul style="list-style-type: none"> <li>1x VGA port</li> </ul>
<b>Serial Port / Header</b>	<ul style="list-style-type: none"> <li>1x COM/Serial</li> </ul>
<b>System BIOS</b>	
<b>BIOS Type</b>	<ul style="list-style-type: none"> <li>128Mb SPI Flash EEPROM with AMI® BIOS</li> </ul>
<b>BIOS Features</b>	<ul style="list-style-type: none"> <li>Plug and Play (PnP)</li> <li>APM 1.2</li> <li>PCI 2.3</li> <li>ACPI 1.0 / 2.0 / 3.0 / 4.0</li> <li>USB Keyboard support</li> <li>SMBIOS 2.7.1</li> <li>UEFI 2.3.1</li> </ul>
<b>Management</b>	
<b>Software</b>	<ul style="list-style-type: none"> <li><u>SuperDoctor® 5</u></li> <li>Watch Dog</li> <li>NMI, SPM, SUM</li> <li>IPMI 2.0</li> <li>Intel Node Manager</li> </ul>
<b>Power Configurations</b>	<ul style="list-style-type: none"> <li>ACPI / APM Power Management</li> <li>Power-on mode for AC power recovery</li> </ul>

**Certification**   **Platinum Certified**  
**[ Test Report ]**

#### PC Health Monitoring

<b>CPU</b>	<ul style="list-style-type: none"> <li>Monitors for CPU Cores, +1.8V, +3.3V, +5V, +12V, +3.3V Standby, +5V Standby, VBAT, Memory, Chipset Voltages.</li> <li>6-Phase-switching voltage regulator</li> </ul>
<b>FAN</b>	<ul style="list-style-type: none"> <li>Total of eight fan headers supporting up to 8 fans</li> <li>8x fans with tachometer status monitoring</li> <li>Status monitor for speed control</li> <li>Pulse Width Modulated (PWM) fan connectors</li> </ul>
<b>Temperature</b>	<ul style="list-style-type: none"> <li>Monitoring for CPU and chassis environment</li> <li>CPU thermal trip support</li> <li>Thermal Control for 8x fan connectors</li> <li>Thermal Monitor 2 (TM2) support</li> <li>PECI</li> </ul>
<b>LED</b>	<ul style="list-style-type: none"> <li>CPU / System Overheat LED</li> <li>Suspend static indicator LED</li> <li>UID/Remote LED</li> </ul>
<b>Other Features</b>	<ul style="list-style-type: none"> <li>Chassis intrusion detection</li> <li>Chassis intrusion header</li> </ul>

#### Operating Environment / Compliance

<b>RoHS</b>	<ul style="list-style-type: none"> <li>RoHS Compliant</li> </ul>
<b>Environmental Spec.</b>	<ul style="list-style-type: none"> <li>Operating Temperature: 10°C to 35°C (50°F to 95°F)</li> <li>Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)</li> <li>Operating Relative Humidity: 8% to 90% (non-condensing)</li> <li>Non-operating Relative Humidity: 5% to 95% (non-condensing)</li> </ul>

## Список деталей

### Parts List - (Items Included)

	Part Number	Qty	Description
<b>Motherboard / Chassis</b>	MBD-X10DRi-T	1	Super X10DRi-T Motherboard
	CSE-745TQ-R920B	1	4U Chassis
<b>Air Shroud</b>	MCP-310-74501-0B	1	SC745 Air Shroud For System with 10G,HF,RoHS/REACH
<b>Backplane</b>	CSE-SAS-743TQ	1	743 SAS BACKPLANE W/AMI MG9072
<b>Cable 1</b>	CBL-0473L	8	SATA,INT,ROUND,ST-ST,21CM,30AWG
<b>Cable 2</b>	CBL-CDAT-0661	2	CBL,SGPIO,2X4F TO 2X4F,P2.54,ROUND CABLE,40CM,28AWG
<b>Label</b>	LBL-0108	1	CAUTION LABEL FOR REDUNDANT PWR SYSTEMS
<b>Manual</b>	MNL-1573-QRG	1	SYS-7048R-TR/SYS-7048R-TRT, QRG,HF,RoHS/REACH,PBF
<b>Parts</b>	MCP-260-00042-0N	1	STD I/O shield for X9 socket R server MB with Gasket.
<b>Heatsink / Retention</b>	SNK-P0048PS	2	2U Passive CPU Heat Sink for X9, X10 Generation Systems Equipped w/ a Narrow ILM MB
<b>Power Supply</b>	PWS-920P-1R	2	1U REDUNDANT 920W PMBus 94% EFFICIENCY

### Optional Parts List

	Part Number	Qty	Description
<b>Storage Controller Card(s) &amp; Cables(s)</b>	AOC-S3008L-L8i & 2x CBL-SAST-0699	-	Standard LP, 8 internal ports (12Gb/s) Gen-3, 63HDD; RAID 0, 1, 10
	AOC-S3008L-L8e & 2x CBL-SAST-0699	-	Standard LP, 8 internal ports (12Gb/s) Gen-3, 122HDD; HBA
	AOC-S3108L-H8IR & 2x CBL-SAST-0699	-	Standard LP, 8 internal ports (12Gb/s) 8x Gen3; RAID 0, 1, 5, 6, 10, 50, 60
	AOC-S3108L-H8IR-16DD & 2x CBL-SAST-0699	-	Standard LP, 8 internal ports (12Gb/s) Gen-3, 16HDD; RAID 0, 1, 5, 6, 10, 50, 60
<b>Mounting Rails</b>	CSE-PT26L-B	1	4U Chassis Rail Kits SC743,745 (w/ 2pcs Black Chassis Ears)
<b>Cable 1</b>	CBL-0178L	-	SATA,INT,FLAT,48CM,26AWG
<b>Cable 2</b>	CBL-0080L	-	big 4 pin to SATA POWER ADAPTER CABLE 6
<b>Peripheral Drive 1</b>	DVM-LITE-DVDRW24-HBT1	-	BLACK LITE-ON 5.25" HH 24X DVD-RW SATA DRIVE PBF
<b>Global Services &amp; Support</b>	<a href="#">OS4HR3/2/1</a>	-	3/2/1-year onsite 24x7x4 service
	<a href="#">OSNBD3/2/1</a>	-	3/2/1-year onsite NBD service
<b>Software</b>	<a href="#">SFT-OOB-LIC</a> • <a href="#">eStore</a>	1	OOB Management Package (per node license)
<b>Software</b>	<a href="#">SFT-DCMS-Single</a>	1	DataCenter Management Package (per node license)

