







# Expansion Enclosure / JBOD



*Versatile capacity expansion and convenient storage scalability*


Infortrend EonStor GS/GSe and EonStor DS systems offer easy scalability on demand, allowing you to increase storage capacity when needed. The JB 3000 series of expansion enclosures (JBODs) are available in multiple form factors, from 2U 12-bay to 4U 60-bay. Their flexibility means they are an excellent choice for diverse environments, budgets, and capacity needs. JB 3000 models deliver extra high speed connectivity to storage systems via 12Gb/s SAS, and all enclosures feature hybrid 2.5"/3.5" drive bays for SSD readiness.



JB 3000 models are offered in single or high availability dual controller configurations and ship with redundant 80 PLUS power supplies by default. For additional energy savings, they employ smart drive spin-down while maintenance is easy with modular hardware. Assured Infortrend reliability is backed by a 3-year warranty.

Product Series	JB 3012	JB 3012A
Photo		
Form factor	2U-12Bay	2U-12Bay
	JB 3012R/S	JB 3012RA/SA
	Note: R: Redundant controller S: Upgradable single controller A: GS type tray	
Host connectivity (per controller)	12Gb/s SAS x 2	
Supported drives	2.5" SAS and SATA SSD 2.5" 10,000 RPM and 15,000 RPM SAS HDD 3.5" 7,200 RPM NL-SAS HDD	
Power supplies	Two redundant 460W	

Product Series	JB 3016	JB 3016A
Photo		
Form factor	3U-16Bay	3U-16Bay
	JB 3016R/S	JB 3016RA/SA
	Note: R: Redundant controller S: Upgradable single controller A: GS type tray	
Host connectivity (per controller)	12Gb/s SAS x 2	
Supported drives	2.5" SAS and SATA SSD 2.5" 10,000 RPM and 15,000 RPM SAS HDD 3.5" 7,200 RPM NL-SAS HDD	
Power supplies	Two redundant 530W	Two redundant 460W

Product Series		JB 3024B	JB 3024BA
Photo			
Form factor	2U-24Bay	JB 3024RB/SB	JB 3024RBA/SBA
Note: <b>R</b> : Redundant controller <b>S</b> : Upgradable single controller <b>A</b> : GS type tray <b>B</b> : 2.5" Form factor			
Host connectivity (per controller)		12Gb/s SAS x 2	
Supported drives		2.5" SAS and SATA SSD 2.5" 10,000 RPM and 15,000 RPM SAS HDD 3.5" 7,200 RPM NL-SAS HDD	
Power supplies		Two redundant 530W	Two redundant 460W

Product Series		JB 3025BA
Photo		
Form factor	2U-25Bay	JB 3025RBA/SBA
Note: <b>R</b> : Redundant controller <b>S</b> : Upgradable single controller <b>A</b> : GS type tray <b>B</b> : 2.5" Form factor		
Host connectivity (per controller)		12Gb/s SAS x 4
Supported drives		2.5" SAS and SATA SSD 2.5" 10,000 RPM and 15,000 RPM SAS HDD 3.5" 7,200 RPM NL-SAS HDD
Power supplies		Two redundant 460W

Product Series		JB 3060	JB 3060L
Photo			
Form factor	4U-60Bay	JB 3060R/G	JB 3060RL/GL
Note: <b>R</b> : Redundant controller <b>G</b> : Non upgradable single controller <b>L</b> : One drawer			
Host connectivity (per controller)		12Gb/s SAS x 3	
Supported drives		2.5" SAS and SATA SSD 2.5" 10,000 RPM and 15,000 RPM SAS HDD 3.5" 7,200 RPM NL-SAS HDD	
Power supplies		Two redundant 1600W	Two redundant 1200W

## WARRANTY AND SERVICE

Standard Service	3-year limited hardware warranty and 8x5 phone, web, and email support (batteries are covered under warranty for 2 years)
Service and Support	Upgrade or Extension Options Warranty extension: Standard service can be extended up to 5 years. The following service can be upgraded to 5 years. <ul style="list-style-type: none"> <li>• Upgrade: Replacement part dispatch on the next business day</li> <li>• Advanced service: 24x7 phone, web, and email support + onsite diagnostics on the next business day</li> <li>• Premium service: 24x7 phone, web, and email support + onsite diagnostics in 4 hours</li> </ul>
	Note: Options may vary by region. For more details, please contact our sales representatives.
	Technical Support
Product Services	Register products, download firmware, apply for licensing services, create product repair tickets, or check product repair status

1. All expansion enclosures are shipped with Standard Service.

2. Options may vary by region.

\* All JBOD 3000 series comply with safety regulations of UL, BSMI, CB, EAC; and electromagnetic compatibility of CE, BSMI, FCC, KC

\* All design and specification declared are subject to change without notice in advance. All rights reserved. Please refer to Infortrend website for further information or localization updates.

Asia Pacific (Taipei, Taiwan)  
Infortrend Technology, Inc.  
Tel : +886-2-2226-0126  
E-mail : sales.ap@infortrend.com

China (Beijing, China)  
Infortrend Technology, Ltd.  
Tel : +86-10-6310-6168  
E-mail : sales.cn@infortrend.com

Japan (Tokyo, Japan)  
Infortrend Japan, Inc.  
Tel : +81-3-5730-6551  
E-mail : sales.jp@infortrend.com

Americas (Sunnyvale, CA, USA)  
Infortrend Corporation  
Tel : +1-408-988-5088  
E-mail : sales.us@infortrend.com

EMEA (Basingstoke, UK)  
Infortrend Europe Ltd.  
Tel : +44(0)-1256-305-220  
E-mail : sales.eu@infortrend.com



© 2022 Infortrend Technology, Inc. All rights reserved. • Any information provided herein is without warranties of any kind of and is subject to change without prior notice. • Infortrend logo, EonStor, SANWatch and EonOne are trademarks or registered trademarks of Infortrend Technology, Inc. • All other names, brands, or services are trademarks or registered trademarks of their respective owners.