




X13SCL-F



Key Features

1. Intel® Xeon® E-2400 Series Processor, Pentium®* Processor, Single Socket LGA-1700 (Socket V0) supported, CPU TDP supports Up to 95W TDP
2. Intel® C262 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
3. Up to 128GB ECC Unbuffered DIMM, DDR5-4400MHz, in 4 DIMM slots
4. 1 PCIe 5.0 x8

1 PCIe 5.0 x8 (in x16)

2 PCIe 4.0 x4 (in x8)
5. Dual LAN with Intel® i210 Gigabit Ethernet Controller
6. **M.2 Interface:** 1 PCIe 4.0 x4

M.2 Form Factor: 2280/22110

M.2 Key: M-Key
7. 4 USB 3.2 Gen1 ports (2 rear + 2 via header)

6 USB 2.0 ports (2 rear+ 4 via header)

1 USB 3.2 Gen1 Type-A header
- ...



Contact Us

Optimized Servers

[SYS-531R-I](#)

Specifications		Resources	Parts List
Product SKUs			
MBD-X13SCL-F			
Physical Stats			
	Form Factor	microATX	
	Dimension	9.6" x 9.6" (24.38cm x 24.38cm)	
Processor			
	CPU	Intel® Xeon® E-2400/Pentium®* Processor Single Socket V0 (LGA-1700) supported, CPU TDP supports Up to 95W TDP *Pentium® G7400 and G7400T	
	Core	Up to 8 cores	
System Memory			
	Memory Capacity	4 DIMM slots Up to 128GB Unbuffered ECC UDIMM, DDR5-4400MT/s	
	Memory Type	4400/4000/3600 MT/s Up to 128GB of memory with speeds of up to 4400MT/s (2DPC)	
	DIMM Sizes	8GB, 16GB, 32GB	
	Memory Voltage	1.1V	
	Error Detection	Corrects single-bit errors Detects double-bit errors (using ECC memory)	
On-Board Devices			
	Chipset	Intel® C262	
	SATA	Intel® C262 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10	
	IPMI	ASPEED AST2600 BMC	
	Graphics	1 Aspeed AST2600 BMC port(s)	
	Network Controllers	Dual LAN with 1GbE with Intel® I210	
Input / Output			
	SATA	8 SATA3 (6Gbps) port(s)	
	LAN	1 RJ45 Dedicated IPMI LAN port	
	USB	6 USB 2.0 port(s) (4 via header; 2 rear) 5 USB 3.2 Gen1 port(s) (2 via header; 2 rear; 1 type A)	
	Video Output	1 VGA D-Sub Connector port(s)	
	Serial Port	2 COM Port(s) (1 header; 1 rear)	
	TPM	1 TPM Header	

Expansion Slots	
PCIe	2 PCIe 4.0 x4 (in x8 slot), 1 PCIe 5.0 x8, 1 PCIe 5.0 x8 (in x16 slot)
M.2	M.2 Interface: 1 PCIe 4.0 x4 Form Factor: 2280/22110 Key: M-Key
System BIOS	
BIOS Type	AMI 32MB AMI UEFI
BIOS Features	ACPI 6.4 SMBIOS 3.5 UEFI 2.8 Plug and Play (PnP) PCI FW 3.3
Management	
Software	SuperCloud Composer , Supermicro Server Manager (SSM) , Supermicro Power Manager (SPM) , Supermicro Update Manager (SUM) , Supermicro SuperDoctor® 5 (SD5) , Super Diagnostics Offline (SDO) , Supermicro Thin-Agent Service (TAS) , SuperServer Automation Assistant (SAA) New! , Plug-ins for 3rd Party Software , IPMI Utilities
Power Configurations	ACPI Power Management, Power-on mode control for AC power loss recovery, Power button override mechanism, Wake-On-LAN
PC Health Monitoring	
Voltage	VBAT, System level control, Supports system management utility, Monitors CPU voltages, Chipset Voltage, Chassis intrusion header, +5V standby, +5V, +3.3V, +12V, Memory Voltages, 7-fan status, +3.3V standby
LED	UID/Remote UID CPU / System Overheat LED
Temperature	Monitoring for CPU and chassis environment CPU thermal trip support PECI
FAN	7x 4-pin fan headers (up to 7 fans) Fan speed control Overheat LED indication 7 fans with tachometer status monitoring
Other Features	WOL, UID, M.2 NGFF connector, Control of power-on for recovery from AC power loss, Chassis intrusion header, ACPI power management
Operating Environment	
Operating Temperature Range	0°C - 50°C (32°F - 122°F)
Non-Operating Temperature Range	-40°C - 70°C (-40°F - 158°F)
Operating Relative Humidity Range	8% - 90% (non-condensing)
Non Operating Relative Humidity Range	5% - 95% (non-condensing)

Certain products may not be available in your region

About Us

Company Profile

Green Computing

Investor Relations

Careers

Site Map

Glossary

News

Press Releases

Supermicro in the News

Product Reviews

Events

Webinars

Resources

Product Briefs

Solution Briefs

Success Stories

Videos

White Papers

Thought Leadership

MySupermicro

Data Center Stories

Connect & Follow

Locations

Contact Us

Newsletter Sign-up

