

GPU SuperServer SYS-422GA-NBRT-LCC

DP Intel 4U Liquid-Cooled System with NVIDIA HGX B200 8-GPU (onsite service is required for liquid-cooling)



Key Applications



High Performance Computing, AI/Deep Learning Training, Industrial Automation, Retail, Healthcare, Conversational AI, Business Intelligence & Analytics, Drug Discovery, Climate and Weather Modeling, Finance & Economics,

Key Features

- Dual Intel® Xeon® 6900 series processors with P-cores, up to 500W TDP, 6UPI;
- Support for up to 8 onboard SXM GPU accelerator cards;
- 24 DIMM slots, ECC DDR5 designed for up to 6400MT/s (1DPC only);
- 2 10G NIC (X710), 1 VGA, 2 USB 3.0, and 1 Dedicated IPMI;
- 8 PCIe 5.0 x16 LP and 2 PCIe 5.0 x16 FHHL;
- Up to 8 front hot-swap 2.5" NVMe drive bays and 2 NVMe M.2;



| | |
|--------------------------|--|
| Form Factor | 4U Rackmount Enclosure: 449 x 174 x 895.35mm (17.6" x 6.85" x 35.25") Package: 1216 x 330 x 670mm (48" x 13" x 26.4") |
| Processor | Dual Socket BR (LGA-7529) Intel® Xeon® 6900 series processors with P-cores Up to 128C/256T; Up to 504MB Cache per CPU |
| GPU | Max GPU Count: Up to 8 onboard GPUs Supported GPU: NVIDIA SXM: HGX B200 8-GPU (180GB) CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect GPU-GPU Interconnect: NVIDIA® NVLink® with NVSwitch™ |
| System Memory | Slot Count: 24 DIMM slots Max Memory (1DPC): Up to 6TB 6400MT/s ECC DDR5 RDIMM Max Memory (1DPC): Up to 6TB 8800MT/s ECC DDR5 MRDIMM |
| Drive Bays Configuration | Default: Total 8 bays <ul style="list-style-type: none"> • 8 front hot-swap 2.5" NVMe drive bays M.2: 2 M.2 NVMe slots (M-key) |
| Expansion Slots | Default <ul style="list-style-type: none"> • 8 PCIe 5.0 x16 LP slots • 2 PCIe 5.0 x16 FHHL slots Option A <ul style="list-style-type: none"> • 8 PCIe 4.0 x16 LP slots • 4 PCIe 5.0 x16 FHHL slots |
| On-Board Devices | Chipset: System on Chip Network Connectivity: 2 RJ45 10GbE with Intel® X710-AT2 |
| Input / Output | 1 VGA port |



| | |
|-----------------------|---|
| System Cooling | Fans: 4 Fan 8cm Fan(s) Liquid Cooling: Direct to Chip (D2C) Cold Plate (optional) |
| Power Supply | 4x 6600W Redundant (2 + 2) Titanium Level (96%) power supplies |
| System BIOS | BIOS Type: AMI 32MB SPI Flash EEPROM |
| Management | SuperCloud Composer; Supermicro Server Manager (SSM); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New! |
| PC Health Monitoring | CPU: Monitors for CPU Cores, Chipset Voltages, Memory 8+4 Phase-switching voltage regulator FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors |
| Dimensions and Weight | Weight: Gross Weight: 136.9 lbs (62.1 kg) Net Weight: 108.2 lbs (49.1 kg) Available Color: Silver |
| Operating Environment | Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing) |
| Motherboard | Super X14DBG-DAP |
| Chassis | CSE-GP403TS-R000NP |