SuperStorage 6038R-DE2CR16L (Complete System Only)

High Availability



Storage Appliance Platform

Integrated Board



Super X10DRS-3U

Views: | Angled View | Front View | Rear View |

Complete System Only: To maintain quality and integrity, this product is sold only as a completely-assembled system (including 4 CPUs, 4 DIMMs, 1 HDD).

▶ Drivers & Utilities
▶ BIOS
▶ IPMI
▶ Tested Memory
▶ Manuals
▶

OS Certification Matrix
▶ Drive Options
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
▶
<

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Key Features (per Node)

Two hot-pluggable systems (nodes) in a 3U form factor. Each node supports the following:

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4[†]/ v3 family; QPI up to 9.6GT/s
- 2. Up to **1TB**[†] ECC 3DS LRDIMM , up to DDR4- **2400**[†]MHz ; 8x DIMM slots
- 3. 3 PCI-E 3.0 x8 (1 FHHL, 2 LPHL) expansion slots per controller; up to 3 add-on cards
- 4. Dual 10GBase-T LAN w/ Intel® X540; 100Mb private Ethernet between controller nodes
- 5. 16x 3.5" Hot-swap SAS3/SATA3 drive bays with SES2
- 6. SAS3 via Broadcom 3008 controller
- 7. Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 8. 12x 4cm PWM cooling fans
- 9. 1200W Redundant Power Supplies Titanium Level (96%)

Product SKUs	Chassis
Motherboard (Two per System)	Dimensions
Processor/Cache (per Node)	Front Panel
System Memory (per Node)	Expansion Slots (per Node)
On-Board Devices (per Node)	Drive Bays
Input / Output (per Node)	Backplane
	System Cooling
	Power Supply (76mm Width)
	System BIOS
	Operating Environment / Compliance

Optional Parts List

	Part Number	Qty	Description
HDD Converter	MCP-220-93707-0B MCP-240-93708-0N	-	Hot-swap 3.5" to 2.5" converter drive tray (for drive slot 1~15) HDD Adapter Bracket for 2.5in SSD/HDD (for drive slot 16)
Global Services & Support	<u>OS4HR3/2/1</u> OSNBD3/2/1		3/2/1-year onsite 24x7x4 service 3/2/1-year onsite NBD service
Software	SFT-OOB-LIC • @Store	1	OOB Management Package (per node license)