

SuperServer 1029U-E1CRTP2 (Complete System Only)



Integrated Board



X11DPU

Views: | [Angled View](#) | [Top View](#) |
| [Front View](#) | [Rear View](#) |

Complete System Only: To maintain quality and integrity, this product is sold only as a completely-assembled system (with minimum 2 CPUs, 4 DIMMs and a storage add-on-card).

[▶ Drivers & Utilities](#) | [▶ BIOS](#) | [▶ IPMI](#) | [▶ Tested Memory](#) | [▶ Tested M.2 List](#) | [▶ Manuals](#) | [▶ OS Certification Matrix](#) | [▶ Compatible GPU List](#) | [▶ Quick-References Guide](#) | [▶ Drive Options](#) | [▶ Network Card \(AOC\) Matrix](#)

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Key Applications

Virtualization
Cloud Computing
High End Enterprise Server

Key Features

1. Dual Socket P (LGA 3647) support 2nd Gen Intel® Xeon® Scalable processors (Cascade Lake/Skylake)[‡]
2. 24 DIMMs; up to 6TB 3DS ECC DDR4-2933MHz[†] RDIMM/LRDIMM, Supports Intel® Optane™ DCPMM^{††}
3. 2 PCI-E 3.0 x16 slots (FH, 10.5" L), 2 PCI-E 3.0 x8 slots (1 LP, 1 internal LP)
4. 2 10G SFP+ and 2 1GbE ports
5. 10 Hot-swap 2.5" drive bays: 10 SAS3/SATA3 ports via Expander and AOC; Optional M.2 NVMe and SATA3 ports
6. 8 heavy duty fans w/ optimal fan speed control
7. 750W Redundant Power Supplies **Platinum Level (94%+)**

Specifications

Product SKUs

- | | |
|--------------------------|---|
| SYS-1029U-E1CRTP2 | <ul style="list-style-type: none"> SuperServer 1029U-E1CRTP2 (Black) |
|--------------------------|---|

Motherboard

Super X11DPU

Processor

- | | |
|------------|---|
| CPU | <ul style="list-style-type: none"> Dual Socket P (LGA 3647) 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors[‡], Dual UPI up to 10.4GT/s Support CPU TDP 70-205W |
|------------|---|

- | | |
|--------------|--|
| Cores | <ul style="list-style-type: none"> Up to 28 Cores |
|--------------|--|

- | | |
|-------------|---|
| Note | <p>[‡] BIOS version 3.2 or above is required to support 2nd Gen Intel® Xeon® Scalable processors (codenamed Cascade Lake-R).</p> |
|-------------|---|

Extended thermal solutions may be required to support CPUs higher than 165W TDP, please contact Supermicro Technical Support for additional information.

System Memory

- | | |
|------------------------|--|
| Memory Capacity | <ul style="list-style-type: none"> 24 DIMM slots Up to 6TB 3DS ECC DDR4-2933MHz[†] RDIMM/LRDIMM Supports Intel® Optane™ DCPMM^{††} |
|------------------------|--|

- | | |
|--------------------|--|
| Memory Type | <ul style="list-style-type: none"> 2933[†]/2666/2400/2133MHz ECC DDR4 RDIMM/LRDIMM 2666 ECC DDR4 NVDIMM |
|--------------------|--|

- | | |
|-------------|---|
| Note | <p>[†] 2933MHz in two DIMMs per channel can be achieved by using memory purchased from Supermicro</p> <p>^{††} Cascade Lake only. Contact your Supermicro sales rep for more info.</p> |
|-------------|---|

On-Board Devices

- | | |
|-----------------------------|--|
| Chipset | <ul style="list-style-type: none"> Intel® C621 chipset |
| SATA | <ul style="list-style-type: none"> SATA3 (6Gbps); RAID 0, 1, 5, 10 |
| Network Connectivity | <ul style="list-style-type: none"> 2 10G SFP+ ports and 2 1GbE ports via AOC-URN2-I4GXS-O (Intel X710-AM2 and Intel i350-AM2) |
| IPMI | <ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support |
| Graphics | <ul style="list-style-type: none"> ASPEED AST2500 BMC |

Input / Output

- | | |
|------------|---|
| SAS | <ul style="list-style-type: none"> 10 SAS3 ports support via expander and storage Add-on Cards |
| LAN | <ul style="list-style-type: none"> 2 10G SFP+ ports 2 RJ45 Gigabit Ethernet ports 1 RJ45 Dedicated IPMI LAN port |

Chassis

- | | |
|--------------------|--|
| Form Factor | <ul style="list-style-type: none"> 1U Rackmount |
|--------------------|--|

- | | |
|--------------|--|
| Model | <ul style="list-style-type: none"> CSE-119UTS-R751P-T |
|--------------|--|

Dimensions and Weight

- | | |
|---------------|---|
| Height | <ul style="list-style-type: none"> 1.7" (43mm) |
|---------------|---|

- | | |
|--------------|---|
| Width | <ul style="list-style-type: none"> 17.2" (437mm) |
|--------------|---|

- | | |
|--------------|---|
| Depth | <ul style="list-style-type: none"> 28.5" (724mm) |
|--------------|---|

- | | |
|---------------|--|
| Weight | <ul style="list-style-type: none"> Net Weight: 26 lbs (11.8 kg) Gross Weight: 41 lbs (18.6 kg) |
|---------------|--|

- | | |
|------------------------|---|
| Available Color | <ul style="list-style-type: none"> Black |
|------------------------|---|

Front Panel

- | | |
|----------------|--|
| Buttons | <ul style="list-style-type: none"> Power On/Off button System Reset button |
|----------------|--|

- | | |
|-------------|---|
| LEDs | <ul style="list-style-type: none"> Power LED Hard drive activity LED Network activity LEDs System Overheat LED / Fan fail LED / UID LED |
|-------------|---|

Expansion Slots

- | | |
|--------------------|---|
| PCI-Express | <ul style="list-style-type: none"> 2 PCI-E 3.0 x16 (Full-height, 10.5" L) 2 PCI-E 3.0 x8 (1 LP, 1 internal LP) <p>(Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and AOC Support for details.)</p> |
|--------------------|---|

Drive Bays / Storage

- | | |
|-----------------|--|
| Hot-swap | <ul style="list-style-type: none"> 10 Hot-swap 2.5" drives supported via expander |
| M.2 | <ul style="list-style-type: none"> 1 M.2 PCI-E 3.0 x4 M-Key NVMe or 1 M.2 M-Key SATA3 (2240/2260/2280/22110) via optional riser card (see optional parts list) 2 M.2 PCI-E 3.0 x4 M-Key NVMe (2260/2280/22110) via optional add-on card AOC-SLG3-2M2 |

System Cooling

- | | |
|-------------|--|
| Fans | <ul style="list-style-type: none"> 8 Heavy duty fans with optimal fan speed control |
|-------------|--|

- | | |
|-------------------|--|
| Air Shroud | <ul style="list-style-type: none"> 1 Air Shroud |
|-------------------|--|


Power Supply

750W Redundant AC-DC Power Supplies, +12V/+12Vsb output

- | | |
|-----------------|--|
| AC Input | <ul style="list-style-type: none"> 100-127Vac, 50-60Hz 200-240Vac, 50-60Hz |
|-----------------|--|

- | | |
|-------------|--|
| +12V | <ul style="list-style-type: none"> Max: 62.5A & Min: 0A (100Vac-127Vac) Max: 62.5A & Min: 0A (200Vac-240Vac) |
|-------------|--|

USB	<ul style="list-style-type: none"> 5 USB 3.0 ports (2 rear, 2 front, 1 Type A)
Video	<ul style="list-style-type: none"> 2 VGA ports (1 rear, 1 onboard)
Serial Port	<ul style="list-style-type: none"> 1 Serial header

12V SB	<ul style="list-style-type: none"> Max: 2.1A Min: 0A
Certification	 Platinum Level [Test Report]

System BIOS

BIOS Type	<ul style="list-style-type: none"> AMI 32Mb SPI Flash ROM
------------------	--

Management

Software	<ul style="list-style-type: none"> Intel® Node Manager Redfish API IPMI 2.0 KVM with dedicated LAN NMI SSM, SPM, SUM SuperDoctor® 5
Power Configurations	<ul style="list-style-type: none"> ACPI Power Management

Operating Environment

RoHS	<ul style="list-style-type: none"> RoHS Compliant
Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)

PC Health Monitoring

CPU	<ul style="list-style-type: none"> Monitors for CPU Cores, Chipset Voltages, Memory. 4+1 Phase-switching voltage regulator
FAN	<ul style="list-style-type: none"> Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors
Temperature	<ul style="list-style-type: none"> Monitoring for CPU and chassis environment Thermal Control for fan connectors

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11DPU	1	Super X11DPU Motherboard
	CSE-119UTS-R751P-T	1	CSE-119UTS-R751P-T Chassis
Add-on Card / Module	AOC-URN2-I4GXS-P	1	1U Ultra Riser 2-port 10GbE SFP+ Intel X710-AM2, and 2-port GbE RJ45, Intel i350-AM2. 1 PCI-E 3.0 x8 (internal) 2 NVMe ports
Backplane	BPN-SAS3-116EL1	1	10-port 1U SAS3 12Gbps single-expander backplane, support up to 10x 2.5-inch SAS3/SATA3 HDD/SSD
Cable 1	CBL-PWEX-0650	1	8 pin female to 2x RA(Right Angle) big 4 pin female power, 47/62CM, 18AWG,RoHS/REACH
Cable 2	CBL-SAST-0532	2	MINI SAS HD,12G,INT,50CM,30AWG
FAN 1	FAN-0101L4	8	40x56,4 Pin PWM,Primary for SC809,111, Sec.for SC816,819,808
Rear Window	MCP-240-81911-0N	1	Rear window for SC819U, 119U tool-less chassis (i4GXS)
Air Shroud	MCP-310-81910-0N	1	Plastic air shroud for SC819U, 119U (X11 24DIMM, left side)
Air Shroud	MCP-310-81911-0N	1	Plastic air shroud for SC819U, 119U (X11 24DIMM, right side)
Riser Card	RSC-R1UW-2E16	1	1U LHS WIO Riser card with two PCI-E x16 slots
Riser Card	RSC-R1UW-E8R	1	1U RHS WIO Riser card with one PCI-E x8 slot
Heatsink / Retention	SNK-P0067PS	2	1U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
* Power Supply	PWS-751P-1R	2	1U 750W Redundant Platinum Single Output Power Supply w/Pmbus W73.5xH40xL203mm,RoHS/REACH

Notes:

- Parts with * are inside the chassis
- Excessive parts might not be shipped, including but not limited to excessive drive trays, fans, riser brackets, air shrouds, IO shields, cables.....etc.

Optional Parts List

	Part Number	Qty	Description
Add-on card for internal M.2 NVMe	AOC-SLG3-2M2	1	Low Profile PCI-E x8 add-on card supports 2 PCI-E 3.0 x4 M-Key M.2 NVMe Modules
Internal Drive Tray for Two 2.5" Drives	MCP-120-82916-0N	1	Internal drive plate Supports Two 2.5" Drive, PCI slots
	CBL-PWEX-0650	1	Power cable for Two internal 2.5" drives
	CBL-0080L	2	
	CBL-0484L Or CBL-SAST-0654 Or	2 1	SATA3 S-S Cable miniSAS(iPass) to 4 SATA Cable
	CBL-SAST-0948	1	miniSAS HD to 4 SATA Cable
2 Internal M.2 slots (1 SATA, 1 NVMe)	RSC-UMR-8 & CBL-SAST-0538	1	1U Ultra RHS Riser Card with 1 PCIE/SATA Hybrid M.2 &1 PCIE X8
Storage Control Card and Cable(s)	AOC-S3008L-L8e	1	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 122HDD, HBA
	AOC-S3008L-L8i		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 63HDD, RAID 0,1,1E
	AOC-S3108L-H8iR		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60
	AOC-S3108L-H8iR-16DD		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 16HDD, RAID 0, 1, 5, 6, 10, 50, 60
Compatible Networking Cables and Transceivers for System default Networking (AOC-URN2-I4GXS)	-	1~2	Networking Cables and Transceivers Compatibility Matrix

Network Card(s)	AOC-SGP-i2/4	-	Standard LP, 2/4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STGN-i1S/i2S	-	Standard LP, 1/2x 10GbE SFP+, PCI-E x8, Intel 82599EN
	AOC-STGF-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel XL710-BM2
	AOC-STG-i4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Intel XL710
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X540
	AOC-STGS-i1/2T	-	Standard LP, 1/2x 10GbE RJ45, PCI-E x8, Intel X550
	AOC-STG-i4T	-	Standard LP, 4x 10GbE RJ45, PCI-E x8, Intel XL710
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel 82598EB
	AOC-S25G-m2S	-	Standard LP, 2x 25GbE SFP28, Mellanox ConnectX-4 LX EN
	AOC-S40G-i2Q	-	Standard LP 2-port 40GbE controller, Intel Fortville XL710
	More	-	AOC Compatibility Matrix
CacheVault(s)	BTR-CV3108-1U1	-	CacheVault for Broadcom 3108 with Supercap mounting in 1U 40x56 fan tray
	BTR-TFM8G-LSICVM02 & BKT-BBU-BRACKET-05	-	CacheVault for Broadcom 3108; Supercap mounting bracket for PCI-E location
1U Cable Management Arm	MCP-290-00152-0N	1	1U Supermicro Cable Management Arm 2nd Gen
TPM security module	AOM-TPM-9670H-S	1	TCG 2.0 compliant trusted platform module (TPM), Horizontal FF
	AOM-TPM-9671H-S	1	TCG 1.2 compliant trusted platform module (TPM), Horizontal FF
Intel VROC RAID Key	AOC-VROCINTMOD	1	Intel VROC, RAID 0, 1, 5, 10 (Intel SSD Only)
	AOC-VROCSTNMOD	1	Intel VROC Standard, RAID 0, 1, 10
	AOC-VROCPREMOD	1	Intel VROC Premium, RAID 0, 1, 5, 10
Global Services & Support	OS4HR3/2/1	-	3/2/1-year onsite 24x7x4 service
	OSNBD3/2/1	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC • eStore	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)