



# EonStor GSe U.2 NVMe All-Flash Storage

*Scale-out Unified Storage for SMB*

## Highlights

### High Performance

- Up to 600K IOPS to accelerate storage operations
- Massive sequential throughput of up to 12GB/s read and 9GB/s write

### Cost-Effective Storage

- Single port U.2 NVMe SSD to deliver better performance at lower costs
- Automated storage tiering to fully utilize SSD and HDD

### Flexible Scalability

- Scale-out and scale-up expansions to easily expand performance and capacity

### Easy to Use and Manage

- Single namespace for easier data access
- Auto-balancing to reduce the burden of storage management for IT staff

## Introduction

*EonStor GSe U.2 NVMe all-flash storage is a high performance unified storage solution with a single controller designed for SMB. Equipped with single port U.2 NVMe SSDs, it delivers high IOPS and throughput at a cost-effective price. This series supports both SAN and NAS services, provides block-level and file-level scale-out expansions to linearly increase performance and capacity, and comes with complete enterprise-grade data protection features that allow IT staff to focus on higher value projects. It thus makes a perfect fit for applications such as database, virtualization, M&E, file sharing, and backup.*

### End-to-End High Performance with U.2 NVMe SSD

Supporting PCIe 4.0, NVMe U.2 SSD, and 100GbE connectivity with RDMA, GSe U.2 NVMe storage delivers a higher speed with a lower latency, providing up to 12GB/s read and 9GB/s write in throughput and 600K on a single appliance.

### Cost-Effectiveness and High Storage Efficiency

U.2 NVMe SSD is becoming the mainstream in the market as it combines the advantages of SAS and SATA SSDs, allowing enterprises to enjoy higher performance at a competitive price.

EonStor GSe U.2 NVMe storage supports hybrid storage, and with automated storage tiering, the storage system can automatically leverage the high throughput and low latency of U.2 NVMe SSDs for frequently accessed data, while using HDDs on expansion enclosures as data backup media, thereby boosting system performance at a reduced total cost of ownership.

EonStor GSe U.2 NVMe storage also comes with inline compression and offline deduplication, which reduces the storage capacity required and thus saves storage costs. The inline compression feature compresses raw files in real-time, which greatly reduces the data size and the transfer time. To deal with repeated files saved by manual backups or archiving, offline deduplication helps you automatically remove duplicate data from a cluster to free up storage space.

## Flexible Scalability with Scale-out and Scale-up

Through scale-out expansion, you can linearly increase performance and capacity for both block-level and file-level data. When one storage appliance is no longer able to provide enough performance or capacity, you can simply add more appliances to form a cluster—with a maximum of 4 appliances.

Through scale-up expansion, each GSe unit can be connected to JBOD expansion enclosures to add up to 896 drives. Together with scale-out expansion, GSe supports more than 3000 drives with over 50PB storage capacity.

## Easy Data Access and Simple IT Management

Users can access shared folders in a single root directory under a single namespace, so that they don't need to worry about where the data is placed. Auto-balancing is also supported to achieve the benefit of load balancing without the burden of manual IT planning and configuration.

## Smart Management for SSD

EonStor GSe U.2 NVMe storage uses an intelligent algorithm to handle data writes and optimize SSD usage. The algorithm not only extends SSD lifespan by reducing the total amount of writes on an SSD but also prevents multiple SSDs from failing at the time and causing data loss. In addition, as EonStor GSe U.2 NVMe storage monitors SSD status in real time, it estimates the remaining lifespan of each SSD and sends the administrator a reminder to replace the SSD that is about to fail.

## Complete Data Protection and Backup

EonStor GSe U.2 NVMe storage offers various data protection mechanisms to guarantee data safety. First, Infortrend's unique RAID technology ensures your data remains intact even in case of a drive failure. With snapshot, a flexible backup tool, you can back up local resources on a storage system by schedule, including volumes and shared folders, and roll back to a previous version when needed. For further protection, you can back up data to a remote GSe appliance using the remote replication feature, or to a public cloud with EonCloud Gateway.

Immutable object storage, another crucial feature for data protection, safeguards data against ransomware attacks. It retains data with WORM (write once read many) storage protection, where data gets "locked" and therefore cannot be modified, deleted, overwritten, or even encrypted by ransomware. By setting a retention period, you can easily follow government compliance requirements or company policies on data retention.

## Availability and Reliability

EonStor GSe U.2 NVMe storage is equipped with dual power supplies and cooling fans to help ensure high data availability. The Cache Backup Module (CBM) consists of a super capacitor and a flash module to prevent data loss during a power interruption or outage.

In addition, EonStor GSe U.2 NVMe storage offers HA service to deliver continuous availability with a near-zero RTO (recovery time objective) and a zero RPO (recovery point objective). With two storage devices deployed at near sites, the HA service provides a block-level active-active storage solution for applications that have an extremely low tolerance for downtime. Featuring synchronous remote replication, auto-failover and failback, this solution ensures identical and complete copies of data are stored on both storage devices and avoids service downtime due to planned or unexpected events.

## Intuitive Management Software

EonStor GSe U.2 NVMe storage adopts EonOne, a web-based management software tool, to assist customers in raising storage and service efficiency for increased productivity. With its intuitive interface design, IT administrators can easily manage a cluster and multiple appliances, monitor performance and capacity usage, and complete system configurations, all from one centralized interface.

# PHYSICAL SPECIFICATIONS

Product Series		GSe 2000U	GSe 3000U	GSe 3000UT	GSe 4000U
Form Factor	2U 24-bay	GSe 2024U	GSe 3024U	GSe 3024UT	GSe 4024U
		Note: U: NVMe storage, T: High performance			
Controller		Single			
Cache Backup Technology (Optional)		Super capacitor + flash module			
CPU		Intel® Xeon® D 2-Core	Intel® Xeon® D 4-Core	Intel® Xeon® D 4-Core	Intel® Xeon® D 6-Core
Cache Memory		Default DDR4 8GB Expandable up to 64GB	Default DDR4 8GB Expandable up to 64GB	Default DDR4 12GB Expandable up to 192GB	Default DDR4 12GB Expandable up to 192GB
Supported Drives		Bundled 2.5" NVMe SSD			
Max. Drive Number	via expansion enclosure, per appliance	896			
	via scale-out with other series of appliances, per cluster	3584			
Onboard 10GbE Ports (SFP+)		0	2	-	-
Onboard 25GbE Ports (SFP28)		-	-	2	-
Max. Host Board Slots		2			
Max. Expansion Boards (12Gb/s SAS x2)		1			
Host Board Options		16Gb/s FC x 4 32Gb/s FC x 2 32Gb/s FC x 4 10GbE (SFP+) x 2 25GbE (SFP28) x 2 12Gb/s SAS x 2		16Gb/s FC x 4 32Gb/s FC x 2 32Gb/s FC x 4 25GbE (SFP28) x 2, RDMA/RoCE 100GbE (QSFP28) x 1, RDMA/RoCE 100GbE (QSFP28) x 2, RDMA/RoCE 12Gb/s SAS x 2	
		Note: 1. One 100GbE x 2 host board delivers a maximum throughput of 100Gb/s. 2. For complete information, refer to our official website for the latest Host Board and Memory Guide.			
Max. 16Gb/s FC Ports		8			
Max. 32Gb/s FC Ports		8			
Max. 10GbE Ports (SFP+)		4	6	-	-
Max. 25GbE Ports (SFP28)		4	4	6	4
Max. 100GbE Ports (QSFP28)		-		2	
Max. 12Gb/s SAS Ports		2			
Expansion Enclosures (JBODs)		JB 3012A, JB 3016A, JB 3024BA, JB 3025BA, JB 3060L			
Dimensions (Without Chassis Ears and Protrusions) (W x H x D)		449 x 88 x 500 mm		449 x 88 x 530 mm	
Package Dimensions (W x H x D)		780 x 338 x 588 mm			
Power Supply Unit	Power Supplies (Redundant and Hot-swappable)	530W x 2 (80 PLUS Bronze)			
	AC Voltage	100VAC @10A to 240VAC @5A			
	Frequency	50-60 Hz			
Safety Standards		<ul style="list-style-type: none"> <li>Electromagnetic Compatibility : CE, BSMI, FCC</li> <li>Safety : UL, BSMI, CB</li> </ul>			

## SOFTWARE SPECIFICATIONS

Max. Logical Drive Number	30	
Max. Logical Drive Capacity	512TB	
Stripe Size	16KB, 32KB, 64KB, 128KB, 256KB, 512KB, or 1024KB per logical drive	
Write Policy	Write-Back or write-through per logical drive.	
Max. Pool Size	2PB	
Max. Pool Number	30	
Max. Volume Size	2PB	
Max. Volume Number	1024	
Max. Host LUN Mapping Number	4096	
Max. Reserved Tag Number (per Host-LUN Connection)	256	
Max. iSCSI Initiators	416	
Max. Host Connection Number (per FC)	128	
RAID Options	RAID 0, RAID 1, RAID 3, RAID 5, RAID 6, RAID 10, RAID 30, RAID 50, RAID 60	
Supported Protocols	File Level	CIFS/SMB (Version 2.0/3.0), NFS (Version 2/3/4), AFP (Version 3.1.12), FTP/FXP (vsftp 2.3.4), WebDAV (httpd package 2.4.6)
	Block Level	FC, iSCSI, SAS
	Object Level	RESTful API
File Level	Max. File System Size	2PB
	Max. Number of User Accounts	20000
	Max. Number of User Groups	512
	Max. Number of Shared Folder	2048 (NFS/CIFS/FTP)   255 (AFP)
	Max. Number of Rsync Jobs	1024
	Max. Number of Concurrent Rsync Processes	64
	Max. Number of Connections	2048 (NFS/CIFS/AFP)   1024 (FTP)
Management	<ul style="list-style-type: none"> <li>• Multi-factor authentication login mechanism</li> <li>• Web-based EonOne management software</li> <li>• User account management</li> <li>• Group management</li> <li>• Folder management - folder access control</li> </ul>	<ul style="list-style-type: none"> <li>• Quota management</li> <li>• Folder encryption with AES</li> <li>• Integration with Microsoft Active Directory (AD) and Linux LDAP</li> <li>• Storage Resource Management to analyze history of resource usage</li> </ul>
Availability and Reliability	<ul style="list-style-type: none"> <li>• Immutable object storage</li> <li>• Hot-swappable hardware modules</li> <li>• Device mapper</li> <li>• Antivirus</li> <li>• Trunk group</li> </ul>	<ul style="list-style-type: none"> <li>• Cache safe technology</li> <li>• UPS</li> <li>• WORM (file level only)</li> <li>• SMB Multichannel</li> </ul>
Efficiency	<ul style="list-style-type: none"> <li>• Inline compression</li> <li>• Offline deduplication</li> </ul>	
Notification	<ul style="list-style-type: none"> <li>• Email</li> <li>• SNMP traps</li> </ul>	
Applications	<ul style="list-style-type: none"> <li>• Web-based file explorer</li> <li>• Syslog server</li> <li>• LDAP server</li> <li>• Proxy server</li> <li>• VPN server</li> <li>• Docker</li> </ul>	
Supported Cloud Services	<p>EonCloud Gateway supports integration with the following cloud providers: Amazon S3, Microsoft Azure, Alibaba Cloud, OpenStack, Baidu Cloud, Google Cloud, Tencent Cloud, Wasabi Cloud, etc.</p> <p>Note: For complete information about cloud provides support, please refer to EonCloud Gateway webpage <a href="https://www.infortrend.com/global/solutions/eoncloud">https://www.infortrend.com/global/solutions/eoncloud</a></p>	
Supported OS	<p>Microsoft Windows Server, Red Hat Enterprise Linux, Mac OS X, VMware.</p> <p>Note: For the latest compatibility details, refer to our official website for the latest Compatibility Matrix.</p>	

## DATA SERVICES

Thin Provisioning	Block level	Default	"Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space.	
File Snapshot		Optional	Snapshot images per folder: 1024	
Local Replication	Snapshot	Block level	Default	Snapshot images per source volume: 64      Snapshot images per pool: 128
			Optional	Snapshot images per source volume: 256      Snapshot images per pool: 4096
	Volume Copy/Mirror		Default	Replication pairs per source volume: 4      Replication pairs per system: 16
			Optional	Replication pairs per source volume: 8      Replication pairs per system: 256
Remote Replication	File level	Default	Rsync with 128-bit SSH encryption	
	Block level	Optional	Replication pairs per source volume: 8      Replication pairs per system: 64	Note: 1. The maximum number of replication pairs per source volume is 8, whether they are remote asynchronous pairs, remote synchronous pairs, or local volume pairs. 2. 16Gb FC x 4, 32Gb FC x 2, and 32Gb FC x 4 host boards do not support Remote Replication.
Automated Storage Tiering		Optional	Storage tiers per pool: 4	
Scale-out	File level	Default	Appliances per cluster: 1	
		Optional	Appliances per cluster: 4	
	Block level	Default	Appliances per cluster: 4	
HA Service	Block level	Optional	Delivering continuous availability and eliminating downtime for mission-critical workloads that require non-stop operations Note: HA Service is not available on GSe 2000U.	
SSD Cache	File level	Default	Accelerating file operations and data access performance for both read and write Max. SSD number per controller: 8	
	Block level	Default	Accelerating data access in random read-intensive environments (e.g. OLTP)	
			Max. SSD number per controller: 4	
			DRAM: 8GB	Max SSD Cache Pool Size: 0.5TB
			DRAM: 16GB	Max SSD Cache Pool Size: 1TB
			DRAM: 32GB	Max SSD Cache Pool Size: 2TB
			DRAM: 64GB and up	Max SSD Cache Pool Size: 4TB

## WARRANTY AND SERVICE

Service and Support	Standard Service	3-year limited hardware warranty and 8x5 phone, web, and email support (batteries are covered under warranty for 2 years)
	Upgrade or Extension Options	Warranty extension: Standard service can be extended up to 5 years. The following service can be upgraded to 5 years. <ul style="list-style-type: none"> <li>• Upgrade: Replacement part dispatch on the next business day</li> <li>• Advanced service: 24x7 phone, web, and email support + onsite diagnostics on the next business day</li> <li>• Premium service: 24x7 phone, web, and email support + onsite diagnostics in 4 hours</li> </ul>
		Note: Options may vary by region. For more details, please contact our sales representatives.
	Technical Support	Get information on system installation and maintenance, download technical documents and software, or issue a support ticket
	Product Services	Register products, download firmware, apply for licensing services, create product repair tickets, or check product repair status

Asia Pacific (Taipei, Taiwan)  
Infotrend Technology, Inc.  
Tel : +886-2-2226-0126  
E-mail : sales.ap@infotrend.com

China (Beijing, China)  
Infotrend Technology, Ltd.  
Tel : +86-10-6310-6168  
E-mail : sales.cn@infotrend.com

Japan (Tokyo, Japan)  
Infotrend Japan, Inc.  
Tel : +81-3-5730-6551  
E-mail : sales.jp@infotrend.com

Americas (Sunnyvale, CA, USA)  
Infotrend Corporation  
Tel : +1-408-988-5088  
E-mail : sales.us@infotrend.com

EMEA (Basingstoke, UK)  
Infotrend Europe Ltd.  
Tel : +44(0)-1256-305-220  
E-mail : sales.eu@infotrend.com

