

Storage A+ Server ASG-2015S-E1CR24L (Complete System Only)

Datasheet Share

2U front/top-loading storage server with 24 hot-swap 3.5" SAS/SATA bays and PCIe 5.0



Key Applications

- Enterprise Server
- HPC, Data Center
- Corporate Database
- iSCSI SAN
- Database Processing & Storage
- Appliance Optimized Storage Building Blocks

Key Features

- Single Socket SP5 AMD EPYC™ 9004/9005 Processor; up to 290W TDP (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- Support up to DDR5 12 DIMM slots (1DPC)
- Dedicated 2 PCIe 5.0 x16 AIOM slots (OCP 3.0 SFF compliant) Up to 6 PCIe 5.0 slots (slot #2 populated by 3808 controller)
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN per node
- 24 Hot-swap 3.5" SAS3/SATA3 drives, 2 Rear SATA slots, 4 Option NVMe slots, 2 NVMe M.2 slots (form factor: 2280/22110)
- 4x 8cm hot-swap counter-rotate redundant PWM cooling fans
- 1600W Redundant Power Supplies Titanium Level (96%)
- HBA Controller support via Broadcom® 3808

[Contact Us](#)

[Get Pricing](#)

Compare

Specifications Resources & Downloads Parts List

Product SKUs

A+ Server **ASG-2015S-E1CR24L**

Motherboard

Super H13SSW

Processor

CPU Single processor(s)
[AMD EPYC™ 9004/9005 Series Processors](#)
(* AMD EPYC™ 9005 Series drop-in support requires board revision 2.x)

Core Count Up to 84C/168T; Up to 384MB Cache

Note Supports 200W - 290W TDP CPUs
* This system supports AMD EPYC™ 9004/9005 Series processors up to 400W TDP

System Memory

Memory Slot Count: 12 DIMM slots
Max Memory (1DPC): Up to 3TB 4800MT/s ECC DDR5 RDIMM (AMD EPYC™ 9004 Series Processor)
Max Memory (1DPC): Up to 4.5TB 6000MT/s ECC DDR5 RDIMM (AMD EPYC™ 9005 Series Processor)
[View Memory Options >](#)

Memory Voltage 1.1V

On-Board Devices

Chipset System on Chip

Network Connectivity Via AIOM
[View AIOM Options >](#)
[View AOC Options >](#)

Input / Output

LAN 1 RJ45 1 GbE Dedicated BMC LAN port

USB 2 USB 3.0 ports (rear)

Video 1 VGA port

System BIOS

BIOS Type AMI 32MB SPI Flash EEPROM

Management

Software [SuperCloud Composer](#)
[Supermicro Server Manager \(SSM\)](#)
[Supermicro Update Manager \(SUM\)](#)
[Supermicro SuperDoctor® 5 \(SD5\)](#)
[Super Diagnostics Offline \(SDO\)](#)
[Supermicro Thin-Agent Service \(TAS\)](#)
[SuperServer Automation Assistant \(SAA\) New!](#)

Power configurations Power-on mode for AC power recovery
ACPI Power Management

Security

Hardware Trusted Platform Module (TPM) 2.0
Silicon Root of Trust (RoT) – NIST 800-193 Compliant

Features Cryptographically Signed Firmware
Secure Boot
Secure Firmware Updates
Automatic Firmware Recovery
Supply Chain Security: Remote Attestation
Runtime BMC Protections
System Lockdown

PC Health Monitoring

CPU Monitors for CPU Cores, Chipset Voltages, Memory
4+1 Phase-switching voltage regulator

FAN Fans with tachometer monitoring
Status monitor for speed control
Pulse Width Modulated (PWM) fan connectors

Temperature Monitoring for CPU and chassis environment
Thermal Control for fan connectors

Chassis

Form Factor 2U Rackmount

Model **CSE-826S3TS-R1K62P1**

Dimensions and Weight

Height 3.5"

Width 17.2"

Depth 34"

Package 12" (H) x 29" (W) x 52" (D)

Weight Gross Weight: 74.5 lbs (33.79 kg)
Net Weight: 52 lbs (23.59 kg)

Available Color Silver

Front Panel

LED Network activity
Power status
SSD activity
System information (overheat/UID)

Buttons Power On/Off

Expansion Slots

PCI-Express (PCIe) Configuration Default
4 PCIe 5.0 x16 FHHL slots
2 PCIe 5.0 x8 FHHL slots
2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible)
Option A
3 PCIe 5.0 x16 FHHL slots
1 PCIe 5.0 x8 FHHL slot
2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible)
Option B
2 PCIe 5.0 x16 FHHL slots
2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible)
[View AOC Options >](#)

Drive Bays / Storage

Drive Bays Configuration Default: Total 26 bays
12 front hot-swap 3.5" SAS/SATA drive bays
12 top-loading hot-swap 3.5" SAS/SATA drive bays
2 rear hot-swap 2.5" SATA drive bays
Option A: Total 28 bays
12 front hot-swap 3.5" SAS/SATA drive bays
12 top-loading hot-swap 3.5" SAS/SATA drive bays
2 rear hot-swap 2.5" SATA drive bays
2 rear hot-swap 2.5" NVMe drive bays
Option B: Total 30 bays
12 front hot-swap 3.5" SAS/SATA drive bays
12 top-loading hot-swap 3.5" SAS/SATA drive bays
4 rear hot-swap 2.5" NVMe drive bays
2 rear hot-swap 2.5" SATA drive bays
[View NVMe Options >](#)
[View Drive Options >](#)

M.2 2 M.2 NVMe slots (M-key 2280/22110)
[View M.2 Options >](#)

System Cooling

Fans 4 Heavy Duty 8cm Fan(s)

Power Supply

1x 1600W Redundant Titanium Level (96%) power supply

Dimension (WxHxL) 73.5 x 40 x 203 mm

Input 1000W: 100-127Vac
1000W: 100-127Vac / 50-60Hz
1600W: 200-240Vac
1600W: 200-240Vac / 50-60Hz

+12V Max: 83.3A / Min: 0A (100Vac-127Vac)
Max: 83A / Min: 0A (100Vac-127Vac)
Max: 133A / Min: 0A (200Vac-240Vac)

12V SB Max: 2.1A / Min: 0A

Output Type Backplanes (gold finger)

Certification **Titanium Level**
[[Test Report](#)]

Operating Environment

ROHS RoHS Compliant

Environmental Spec. Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F)
Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)
Operating Relative Humidity: 8% to 90% (Non-Condensing)
Non-operating Relative Humidity: 5% to 95% (Non-Condensing)

Certain products may not be available in your region

Global SKU English

About Us

Company Profile
Green Computing
Investor Relations
Careers
Site Map
Glossary

News

Press Releases
Supermicro in the News
Product Reviews
Events
Webinars

Resources

Product Briefs
Solution Briefs
Success Stories
Videos
White Papers
Thought Leadership
MySupermicro
Data Center Stories

Connect & Follow

Locations
Contact Us
Newsletter Sign-up

