


## G292-2G0

HPC Server - 2U DP 16 x GPUs

intel  
XEON



### Features

- Supports up to 16 x single slot GPU cards
- 3rd Gen. Intel® Xeon® Scalable Processors
- 8-Channel RDIMM/LRDIMM DDR4 per processor, 24 x DIMMs
- Dual ROM technology supported
- 2 x 10Gb/s BASE-T LAN ports (Intel® X710-AT2)
- 1 x Dedicated management port
- 4 x 2.5" SATA/SAS hot-swappable HDD/SSD bays
- 4 x 2.5" SATA/SAS/Gen4 NVMe hot-swappable HDD/SSD bays
- 2 x PCIe x16 Half-length low-profile slots for add-on cards
- Aspeed® AST2600 management controller
- Dual 3200W 80 PLUS Platinum hot-swap power supply

### Specification

<b>Dimensions</b>	2U (W448 x H87.5 x D800 mm)	<b>Rear I/O</b>	2 x USB 3.0, 1 x VGA, 2 x RJ45, 1 x MLAN
<b>Motherboard</b>	MG52-G20	<b>Backplane I/O</b>	8 x SAS/SATA/Gen4 NVMe ports Bandwidth: SATAIII 6Gb/s, SAS 12Gb/s or PCIe Gen4 x4
<b>CPU</b>	3rd Gen Intel® Xeon® Scalable Processors Intel® Xeon® Platinum Processor, Intel® Xeon® Gold Processor, Intel® Xeon® Silver Processor 10nm technology, CPU TDP up to 270W 2 x LGA 4189 (Socket P+)	<b>TPM</b>	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
<b>Chipset</b>	Intel® C621A Express Chipset	<b>Power Supply</b>	2+0 3200W 80 PLUS Platinum hot-swap power supply AC Input: 100-240V
<b>Memory</b>	8-Channel DDR4 memory, 24 x DIMM slots RDIMM modules up to 64GB supported LRDIMM modules up to 128GB supported 3DS RDIMM/LRDIMM modules up to 256GB supported 1.2V modules: 3200/2933/2666 MHz	<b>System Management</b>	Aspeed® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
<b>LAN</b>	2 x 10Gb/s BASE-T LAN ports (Intel® X710-AT2) 1 x 10/100/1000 management LAN	<b>OS Compatibility</b>	Windows Server 2016 / 2019 RHEL 8.2 (x64) / 8.3 (x64) or later SLES 12 SP5 (x64) / 15 SP2 (x64) or later Ubuntu 20.04 LTS (x64) / 20.04.1 LTS (x64) or later VMware ESXi 6.7 Update3 P03 / 7.0 Update2
<b>Video</b>	Integrated in Aspeed® AST2600 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM	<b>System Fans</b>	8 x 80x80x38mm (16300rpm)
<b>Storage</b>	4 x 2.5" SATA/SAS hot-swappable HDD/SSD bays 4 x 2.5" SATA/SAS/Gen4 NVMe hot-swappable HDD/SSD bays SAS card is required for SAS devices support	<b>Operating Properties</b>	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
<b>Expansion Slots</b>	16 x PCIe x16 single slots (Gen4 x16 bus) for GPUs 2 x PCIe x16 (Gen4 x16 bus) Half-length low-profile slots	<b>Package Contents</b>	1 x G292-2G0 system, 2 x CPU heatsinks, 1 x Rail kit
<b>Front I/O</b>	-	<b>Reference Numbers</b>	Barebone with rail kit: 6NG2922G0MR-00 - Motherboard: 9MG52G20NR-00 - Tool-less rail kit: 25HB2-A86102-K0R - Power supply: 25EPO-222001-D0S



Learn more about GIGABYTE server solutions, visit [www.gigabyte.com/Enterprise](http://www.gigabyte.com/Enterprise)

\* All specifications are subject to change without notice. Please visit our website for the latest information.

\* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.

\* All other brands, logos and names are property of their respective owners.

© 2021 GIGABYTE Technology Co., Ltd. All rights reserved.