

# SuperStorage 927R-E2CJB



High Availability



Storage Appliance Platform

**2 Integrated AOM**



**AOM-SAS3-927EL-JB**

Views: | [Angled View](#) | [Top View](#) |  
| [Front View](#) | [Rear View](#) |

[▶ Drive Options](#) ▶ [Manuals](#)

## Key Features

**Two hot-pluggable systems (nodes) in a 2U form factor.**

1. High Availability Storage Appliance Platform
2. Redundant Hot-swap expander trays
3. 4 SAS3.0 IO ports
4. 24 Hot-swap 2.5" Drive Bays
5. IPMI 2.0 with dedicated LAN
6. 8x 40mm cooling fans
7. 1200W Redundant Power Supplies Titanium Level Certified

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

**Product SKUs**

**Add-on Module**

**Drive Bays**

**Expander**

**On-Board Devices**

**Front Panel**

**Chassis**

**Dimensions**

**System Cooling**

**Power Supply (76mm Width)**

**Operating Environment / Compliance**

## Parts List - (Items Included)

	Part Number	Qty	Description
<b>Add-on-module / Chassis</b>	AOM-SAS3-927EL-JB	1	Super AOM-SAS3-927EL-JB
	CSE-927ETS-R0JNDBP-X10	1	2U Chassis
<b>Add-on Card / Module</b>	AOM-SAS3-927EL-JB-P	2	SAS3 Expander card support SBB 2U JBOD system, for 24x 2.5-inch SAS3/SAS2/SATA3 drives
<b>Backplane</b>	BPN-SAS3-927-N4	1	24-port 2U SBB SAS3 12Gbps midplane, support up to 20x 2.5-inch SAS3/SATA3 HDD/SSD and 4x NVMe/SAS3/SATA3 storage devices
<b>Cable 1</b>	CBL-0160L	2	NEMA5-15P to C13 US power cord 16AWG 6ft, PBF (default for high watt)
<b>Cable 2</b>	CBL-PWCD-0160-IS	2	PWCD,US,NEMA5-15P TO IEC60320 C13,6FT,16AWG,13A,125V,RoHS/REACH
<b>Label</b>	LBL-0108	1	CAUTION LABEL FOR REDUNDANT PWR SYSTEMS
<b>Fan</b>	FAN-0157L4	8	40x40x56 mm 13K-11K RPM Counter-rotating Fan w/ a 160-mm Wire Coming out from the Fan Inlet Side,RoHS/REACH
<b>Tray(s)</b>	MCP-220-92701-0N	24	Drive trays support 2.5" SAS HDD/SSD
<b>Power Supply</b>	PWS-1K23A-1R	2	1200W Redundant Titanium Power Supplies

## Optional Parts List

	Part Number	Qty	Description
<b>Global Services &amp; Support</b>	<u>OS4HR3/2/1</u>	-	3/2/1-year onsite 24x7x4 service
	<u>OSNBD3/2/1</u>	-	3/2/1-year onsite NBD service