



EonStor DS U.2 NVMe All-Flash Storage

Enterprise-Class High Reliability SAN Storage

Highlights

Extreme Performance

- Up to 1000K IOPS
- Up to 11 GB/s read and 7.5 GB/s write

Great Scalability

- Up to 488 drives via expansion

Storage Efficiency

- Auto storage tiering to balance cost with performance between SSDs and HDDs

Smart SSD Management

- Extends SSD lifespan
- Prevents simultaneous failure of multiple SSDs and resulting data loss
- Timely reminder for SSD replacement

Intuitive Management

- Web-based software SANWatch simplifies management effort

Introduction

EonStor DS U.2 NVMe all-flash storage is high performance SAN storage for enterprises. Equipped with U.2 NVMe SSDs, it delivers high IOPS and throughput that are especially suitable for SAN environments at a cost-effective price. With advanced data services, this series makes a perfect fit for applications requiring both performance and capacity, such as database, virtualization, and VDI.

High Performance and Scalability

Featuring the mainstream ultra-speed U.2 NVMe SSDs, EonStor DS U.2 NVMe storage delivers up to 1000K end-to-end IOPS to accelerate storage operations, with a massive sequential throughput at up to 11 GB/s read and 7.5 GB/s write. By adding expansion enclosures (JBODs) to the storage appliance, storage capacity can be flexibly scaled up with a maximum of 448 drives, including SSDs and HDDs.

Storage Efficiency with Better TCO

EonStor DS U.2 NVMe storage supports hybrid storage, and with automated storage tiering, the storage system can automatically leverage the high performance I/Os of U.2 NVMe SSDs for frequently accessed data, and use NL-SAS/SATA HDDs on expansion enclosures for massive data archive, thereby boosting system performance at a reduced total cost of ownership (TCO).

In addition, EonStor DS U.2 NVMe storage comes with offline deduplication and compression, which reduces the overall storage capacity required and thus saves further costs.

Intelligent Management of SSDs

EonStor DS U.2 NVMe storage uses an intelligent algorithm to handle data writes and optimize SSD usage. The algorithm not only extends SSD lifespan by reducing the total amount of writes on an SSD but also prevents multiple SSDs from failing at the same time, thereby preventing the resulting data loss. In addition, as the system monitors SSD status in real time, it estimates the remaining lifespan of each SSD and sends the administrator a reminder to replace the SSD that is about to fail.

Flexible Choice of Host Interfaces

To satisfy the needs of different environments, EonStor DS U.2 NVMe storage supports various I/O cards called host boards, which come in Fibre Channel 16/32 Gb/s, iSCSI 10/25 Gb/s, and SAS 12 Gb/s interfaces.

Complete Data Protection and Backup

EonStor DS U.2 NVMe storage offers various data protection mechanisms to guarantee data safety. First, Infortrend's unique RAID technology ensures your data remains fully protected in case of a drive failure. With snapshot, a flexible backup tool, you can back up local data on a storage system by schedule and roll back to a previous version any time. For further security, you can back up data to a remote DS appliance using the remote replication feature, available in synchronous and asynchronous modes.

High Reliability Hardware Design

From power supplies, cooling fans, controllers, to host boards, the modular design of all these hardware components lowers maintenance complexity and provides fast, precise technical support and RMA services, keeping EonStor DS U.2 NVMe storage safe from any downtime to bring non-stop services, increased productivity, and competitiveness.

Intuitive Management Software

EonStor DS U.2 NVMe storage adopts SANWatch, the web-based management software for DS appliances, to assist customers in raising storage and service efficiency for increased productivity. With its intuitive interface design, IT administrators can easily manage multiple appliances, monitor performance and capacity usage, and complete system configurations, all from one centralized interface.

PHYSICAL SPECIFICATIONS

Product Series		DS 4000U			
Form Factor	2U 24-bay	DS 4024UG	DS 4024UGT	DS 4024UR	DS 4024URT
		Note: U : U.2 NVMe Storage, R : Redundant controller, G : Single controller, T : High performance			
Controller		Single		Dual redundant	
Cache Backup Technology		Super capacitor + flash module (optional for single controller)			
CPU		Intel® Xeon® D 2-Core	Intel® Xeon® D 4-Core	Intel® Xeon® D 2-Core	Intel® Xeon® D 4-Core
Cache Memory (per System)		Default DDR4 4GB Expandable up to 64GB		Default DDR4 8GB Expandable up to 128GB	
Supported Drives		Bundled 2.5" U.2 NVMe SSD			
		Note: For the latest compatibility details, refer to our official website for the latest Compatibility Matrix.			
Max. Drive Number		448			
Onboard 12Gb/s SAS Ports (For JBOD Expansion)		2			
Onboard 10GbE Ports (SFP+)		0	2	0	4
Max. Host Board Slots		2		4	
Host Board Options		16Gb/s FC x 4 32Gb/s FC x 2 32Gb/s FC x 4		10GbE (SFP+) x 2 25GbE (SFP28) x 2 12Gb/s SAS x 2	
		Note: For complete information, refer to our official website for the latest Host Board and Memory Guide.			
Max. 16Gb/s FC Ports		16			
Max. 32Gb/s FC Ports		16			
Max. 10GbE Ports (SFP+)		4	6	8	12
Max. 25GbE Ports (SFP28)		8			
Expansion Enclosures (JBODs)		JB 3012, JB 3016, JB 3024B, JB 3025B, JB 3060L			
Dimensions (Without Chassis Ears / Protrusions) (W x H x D)		449 x 88 x 500 mm			
Package Dimensions (W x H x D)		780 x 338 x 588 mm			
Power Supply Unit	Power Supplies (Redundant and Hotswappable)	530W PSU (80 PLUS Bronze, 80 PLUS Gold for EU)			
	AC voltage	100VAC @10A to 240VAC @5A			
	Frequency	50-60 Hz			
Safety Standards		<ul style="list-style-type: none"> Electromagnetic Compatibility: CE, BSMI, FCC Safety: UL, BSMI, CB 			

SOFTWARE SPECIFICATIONS

Max. Logical Drive Number	32
Max. Logical Drive Capacity	512TB
Stripe Size (per Logical Drive)	16KB, 32KB, 64KB, 128KB, 256KB, 512KB, 1024KB
Write Policy (per Logical Drive)	Write-back or write-through
Max. Logical Volume Size	512TB
Max. Logical Volume Number	32
Max. Partition Size	512TB
Max. Partition Number (per Logical Volume / per System)	2048/1024
Max. Host-LUN Mapping Number	4096
Max. Reserved Tag Number (per Host-LUN Connection)	256
Max. iSCSI Sessions (per Controller)	416
RAID Options	RAID 0, RAID 1, RAID 3, RAID 5/5F, RAID 6/6F, RAID 10, RAID 30, RAID 50, RAID 60
Supported Protocols	FC, iSCSI, SAS
Management	<ul style="list-style-type: none"> Web-based SANWatch management software Embedded RAIDWatch Terminal via RS-232C Telnet/SSH
Availability and Reliability	<ul style="list-style-type: none"> Hot-swappable hardware modules Trunk group Device mapper Cache safe technology
Efficiency	<ul style="list-style-type: none"> Offline compression Offline deduplication
Notification	<ul style="list-style-type: none"> Email SNMP traps
Supported OS	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise, Sun Solaris, Mac OS X, Vmware Note: For OS version support, please refer to the Compatibility Matrix.

DATA SERVICES

Thin Provisioning	Default	"Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space.	
Local Replication	Snapshot	Default	Snapshot images per source partition: 64 Snapshot images per pool: 128
		Optional	Snapshot images per source partition: 256 Snapshot images per pool: 4096
	Volume Copy/Mirror	Default	Replication pairs per source volume: 4 Replication pairs per system: 16
		Optional	Replication pairs per source volume: 8 Replication pairs per system: 64
Remote Replication	Optional	Replication pairs per source volume: 8 Replication pairs per system: 64	
		Note: 1. The maximum number of replication pairs per source volume is 8, whether they are remote asynchronous pairs, remote synchronous pairs, or local volume pairs 2. 16Gb FC x 4, 32Gb FC x 2, and 32Gb FC x 4 host boards do not support Remote Replication.	
Automated Storage Tiering	Optional	2 or 4 storage tiers based on drive types	

WARRANTY AND SERVICE

Service and Support	Standard Service	3-year limited hardware warranty and 8x5 phone, web, and email support (batteries are covered under warranty for 2 years)
	Upgrade or Extension Options	<p>Warranty extension: Standard service can be extended up to 5 years. The following service can be upgraded to 5 years.</p> <ul style="list-style-type: none"> Upgrade: Replacement part dispatch on the next business day Advanced service: 24x7 phone, web, and email support + onsite diagnostics on the next business day Premium service: 24x7 phone, web, and email support + onsite diagnostics in 4 hours <p>Note: Options may vary by region. For more details, please contact our sales representatives.</p>
	Technical Support	Get information on system installation and maintenance, download technical documents and software, or issue a support ticket
	Product Services	Register products, download firmware, apply for licensing services, create product repair tickets, or check product repair status

Asia Pacific (Taipei, Taiwan)
Infotrend Technology, Inc.
Tel : +886-2-2226-0126
E-mail : sales.ap@infotrend.com

China (Beijing, China)
Infotrend Technology, Ltd.
Tel : +86-10-6310-6168
E-mail : sales.cn@infotrend.com

Japan (Tokyo, Japan)
Infotrend Japan, Inc.
Tel : +81-3-5730-6551
E-mail : sales.jp@infotrend.com

Americas (Sunnyvale, CA, USA)
Infotrend Corporation
Tel : +1-408-988-5088
E-mail : sales.us@infotrend.com

EMEA (Basingstoke, UK)
Infotrend Europe Ltd.
Tel : +44(0)-1256-305-220
E-mail : sales.eu@infotrend.com

