

# Storage SuperServer SSG-641E-E1CR24H

Datasheet Share

4U front-loading storage server with 24 hot-swap 3.5" SAS/SATA bays (6 optional NVMe hybrid, SAS hardware RAID) and PCIe 5.0



### Key Applications

- Enterprise Server
- HPC, Data Center
- Corporate Database
- iSCSI SAN
- Database Processing & Storage
- Appliance Optimized Storage Building Blocks

### Key Features

- Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s(1DPC) in 16 DIMM slots
- 2x 10 GbE onboard via Broadcom BCM57416
  - 1x GbE Dedicated LAN for server remote management: IPMI 2.0 / KVM over LAN / Media over LAN

[Get Pricing](#)

[Contact Us](#)

## Specifications Resources & Downloads Parts List

### Product SKUs

SuperServer **SSG-641E-E1CR24H**

### Motherboard

**Super X13DEI-T**

### Processor

**CPU** Dual Socket E (LGA-4677)  
[5th Gen Intel® Xeon®](#) / [4th Gen Intel® Xeon® Scalable processors](#)

**Note** Supports up to 270W TDP CPUs (Air Cooled)

### System Memory

**Memory** Slot Count: 16 DIMM slots  
 Max Memory (1DPC): Up to 4TB 5600MT/s ECC DDR5 RDIMM  
[View Memory Options >](#)

**Memory Voltage** 1.1V

### On-Board Devices

**Chipset** Intel® C741

**Network Connectivity** 2 RJ45 10GbE with Broadcom® BCM57416  
[View AOC Options >](#)

### Input / Output

**LAN** 1 RJ45 1 GbE Dedicated BMC LAN port  
 2 RJ45 10 GbE LAN ports (Broadcom® BCM57416) (IPMI shared on LAN port 1)

**USB** 4 USB 3.0 ports(rear)

**Video** 1 VGA port(Rear)

**Serial** 1 COM port(Rear)

**TPM** 1 TPM header

### System BIOS

**BIOS Type** AMI 32MB SPI Flash EEPROM

### Management

**Software** [SuperCloud Composer](#)  
[Supermicro Server Manager \(SSM\)](#)  
[Supermicro Update Manager \(SUM\)](#)  
[Supermicro SuperDoctor® 5 \(SD5\)](#)  
[Super Diagnostics Offline \(SDO\)](#)  
[Supermicro Thin-Agent Service \(TAS\)](#)  
[SuperServer Automation Assistant \(SAA\) New!](#)

**Power configurations** Power-on mode for AC power recovery  
 ACPI Power Management

### Security

**Hardware** Trusted Platform Module (TPM) 2.0  
 Silicon Root of Trust (RoT) – NIST 800-193 Compliant

**Features** Cryptographically Signed Firmware  
 Secure Boot  
 Secure Firmware Updates  
 Automatic Firmware Recovery  
 Supply Chain Security: Remote Attestation  
 Runtime BMC Protections  
 System Lockdown

### PC Health Monitoring

**CPU** Monitors for CPU Cores, Chipset Voltages, Memory  
 7+1 Phase-switching voltage regulator

**FAN** Fans with tachometer monitoring  
 Status monitor for speed control  
 Pulse Width Modulated (PWM) fan connectors

**Temperature** Monitoring for CPU and chassis environment  
 Thermal Control for fan connectors

### Chassis

**Form Factor** 4U Rackmount

**Model** CSE-846BTS-R1K23BP5

### Dimensions and Weight

**Height** 7"

**Width** 17.2"

**Depth** 26"

**Package** 15" (H) x 27" (W) x 39" (D)

**Weight** Gross Weight: 92 lbs (41.7 kg)  
 Net Weight: 55 lbs (24.9 kg)

**Available Color** Silver

### Front Panel

**LED** HDD activity  
 Network activity  
 Power status  
 System information (overheat/UID)

**Buttons** Power On/Off

### Expansion Slots

**PCI-Express (PCIe) Configuration** Default  
 4 PCIe 5.0 x16 (in x16) FHHL slots  
 2 PCIe 5.0 x8 (in x8) FH/10.5"L slots  
[View AOC Options >](#)

### Drive Bays / Storage

**Drive Bays Configuration** Default: Total 26 bays  
 24 front hot-swap 3.5" SAS/SATA drive bays  
 2 rear hot-swap 2.5" SATA drive bays  
 Option A: Total 6 bays  
 6 front hot-swap 3.5" NVMe\* drive bays  
 (\*NVMe support may require additional storage controller and/or cables, please see the optional parts list for details)  
[View NVMe Options >](#)  
[View Drive Options >](#)

**M.2** 2 M.2 PCIe 4.0 x2 NVMe slots (M-key 2280/22110)  
[View M.2 Options >](#)

### System Cooling

**Fans** 5 Heavy Duty 8cm Fan(s)

### Power Supply

2x 1200W Redundant Titanium Level (96%) Hot-plug power supplies

**Dimension (WxHxL)** 76 x 40 x 336 mm

**Input** 1000W: 100-127Vac  
 1000W: 100-127Vac / 50-60Hz  
 1200W: 200-240Vac  
 1200W: 200-240Vac / 50-60Hz  
 1200W: 200-240Vdc / 50-60Hz (for CCC only)

**+12V** Max: 83A / Min: 0A (100Vac-127Vac)  
 Max: 100A / Min: 0A (200Vdc-240Vdc)  
 Max: 100A / Min: 0A (200Vac-240Vac)

**5V SB** Max: 4A / Min: 0A

**Output Type** Backplanes (gold finger)

### Operating Environment

**ROHS** RoHS Compliant

**Environmental Spec.** Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F)  
 Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)  
 Operating Relative Humidity: 8% to 90% (Non-Condensing)  
 Non-operating Relative Humidity: 5% to 95% (Non-Condensing)

How easy is it to find the information you are looking for? \*

- Very easy  Easy  Neutral  Difficult  Very difficult

[Submit](#)

Certain products may not be available in your region

Global SKU [English](#)

### About Us

- Company Profile
- Green Computing
- Investor Relations
- Careers
- Site Map
- Glossary

### News

- Press Releases
- Supermicro in the News
- Product Reviews
- Events
- Webinars

### Resources

- Product Briefs
- Solution Briefs
- Success Stories
- Videos
- White Papers
- Thought Leadership
- MySupermicro
- Data Center Stories

### Connect & Follow

- Locations
- Contact Us
- Newsletter Sign-up

