

SuperServer E403-9D-16C-IP



Integrated Board



Super X11SDW-16C-TP13F

Views: | [Angled View](#) | [Top View](#) | [IO View](#) |
| [Top View 1](#) | [Top View 2](#) |

▶ [Drivers & Utilities](#) ▶ [BIOS](#) ▶ [IPMI](#) ▶ [Tested Memory](#) ▶ [Manuals](#) ▶
[Quick-References Guide](#) ▶ [Tested M.2 List](#)

Note: Image above may show a varied configuration of optional parts.
Please refer to parts list for standard parts included.



Key Applications

5G Radio Access Network (RAN)
Multi-Access Edge Computing (MEC)
Edge AI Inferencing
Vehicle to Everything (C-V2X/V2X)
Virtualized Functions and Services

Key Features

1. Intel® Xeon® D-2183IT Processor,
16 Cores, 32 Threads, 2.2 GHz, 100W
2. Operating Temperature
-40°C ~ 46°C + Solar load
(-40°F ~ 114.8°F + Solar load)
3. GR-487-CORE compliant
4. Tamperproof design
5. Noise 71 dBA
6. 100-240 Vac, Est. Max
Power consumption: 1200W
(instantaneous)/ 900W (stable)
7. 620W heater (Initiating power: 900W)

Product SKUs

Motherboard

Processor

System Memory

On-Board Devices

Input / Output

System BIOS

Management

Chassis

Dimensions and Weight

Front Panel

Expansion Slots

Drive Bays

System Cooling

Power Supply

Operating Environment / Compliance