SuperStorage 6049P-E1CR45L+ (Complete System Only)



Integrated Board



Super X11DSC+

Views: | <u>Angled View</u> | <u>Top View</u> | | <u>Front View</u> | <u>Rear View</u> |

Complete System Only: To maintain quality and integrity, this product is sold only as a completely-assembled system (with minimum 2 CPUs, 2 DIMMs, 12 HDDs and 1 NIC or SIOM card).

 ▶ Drivers & Utilities
 ▶ BIOS
 ▶ IPMI
 ▶ Tested Memory
 ▶ NVMe

 Options
 ▶ Manuals
 ▶ OS Certification Matrix
 ▶ Drive Options
 ▶

 Tested SIOM
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶
 ▶

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Key Features

- Corporate Database
- Database Processing & Storage
- Enterprise Server
- HPC, Data Center
- iSCSI SAN
- 1. Dual Socket P (LGA 3647) support 2nd Gen Intel® Xeon® Scalable processors (Cascade Lake/Skylake)[‡]
- 24 DIMMs; up to 6TB 3DS ECC DDR4-2933MHz[†] RDIMM/LRDIMM, Supports Intel® Optane[™] DCPMM^{††}
- 3. 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8, 1 <u>SIOM</u> card support (flexible networking) Note: must bundle with Network card
- 4. 45 Hot-swap 3.5" SAS3/SATA3 drive bays with SES3 (can support 2.5" without converter tray); 2 rear Hot-swap 2.5" drive bays; optional 6 NVMe bays
- 5. Broadcom 3616, IT mode, x16 SAS
- 6. Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 7. 5 Hot-swap 8cm rear exhaust PWM fans
- 8. 1600W Redundant Power Supplies Platinum Level (94%)

Product SKUs	Chassis
Motherboard	Dimensions
Processor/Cache	Front Panel
System Memory	Expansion Slots
On-Board Devices	Drive Bays
Input / Output	Backplane
System BIOS	System Cooling
Management	Power Supply
PC Health Monitoring	Operating Environment Compliance

Optional Parts List

	Part Number	Qty	Description
6 NVME Bays	AOC-SLG3-2E4R-O MCP-220-94607-0N CBL-SAST-0818 CBL-SAST-0850	$\frac{1}{1}$ $\frac{4}{2}$	NVMe AOC SC946S NVMe kits w/ cage, tray, cable, BPN (no NVMe cable)OCuLink v.91,INT,PCIe NVMe SSD, 55CM,34AWG 55cm OCuLink to OCuLink Cable OCuLink to MiniSAS HD V.91, INT, PCIe NVMe SSD, 37CM, 15D15F7D, 34AWG
Global Services & Support	OS4HR3/2/1 OSNBD3/2/1	-	3/2/1-year onsite 24x7x4 service 3/2/1-year onsite NBD service
Software	SFT-OOB-LIC • @Store	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)
SIOM Network Card(s)	AOC-MGP-12 AOC-MGP-14 AOC-MTG-12T AOC-MTG-14T AOC-MTGN-12S AOC-MTG-14S	- - - - - - -	SIOM 2-port GbE, Intel i350-AM2 SIOM 4-port GbE, Intel i350-AM4 SIOM 2-port 10GBase-T, Intel X550 SIOM 4-port 10GBase-T, Intel X550 SIOM 2-port 10G SFP+, Intel 82599ES SIOM 4-port 10G SFP+, Intel XL710