

SuperServer 6029U-TR4T (Complete System Only)



Integrated Board



Super X11DPU

Views: | [Angled View](#) | [Top View](#) |
| [Front View](#) | [Rear View](#) |

Complete System Only: To maintain quality and integrity, this product is sold only as a completely-assembled system (with minimum 2 CPUs and 4 DIMMs).

[▶ Drivers & Utilities](#) | [▶ BIOS](#) | [▶ IPMI](#) | [▶ Tested Memory](#) | [▶ Tested M.2 List](#) | [▶ NVMe Options](#) | [▶ Manuals](#) | [▶ OS Certification Matrix](#)
[▶ Compatible GPU List](#) | [▶ Quick-References Guide](#) | [▶ Drive Options](#) | [▶ Network Card \(AOC\) Matrix](#)

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Key Applications

Virtualization
Hyperconverge Storage
Cloud Computing
High End Enterprise Server
Flexible Networking Options

Key Features

1. Dual Socket P (LGA 3647) support
2nd Gen Intel® Xeon® Scalable processors (Cascade Lake/Skylake)‡
2. 24 DIMMs; up to 6TB 3DS ECC DDR4-2933MHz† RDIMM/LRDIMM, Supports Intel® Optane™ DCPMM††
3. 2 PCI-E 3.0 x16 slots (FH, 10.5" L),
4 PCI-E 3.0 x8 slots (FH, 10.5" L),
1 PCI-E 3.0 x8 slot (LP)
4. 4x 10GBase-T LAN ports via Intel X710-BM1
5. 12 Hot-swap 3.5" drive bays:
12 SATA (opt. 8 SAS3 + 4 NVMe/SAS3),
Optional 2 hot-swap 2.5" rear drive bays for SSDs;
Optional M.2 NVMe and SATA3 ports
6. 4 Heavy duty 8cm fans
7. 1000W High efficiency (96%)
Redundant PSU; **Titanium Level**

Specifications

Product SKUs

SYS-6029U-TR4T ■ SuperServer 6029U-TR4T (**Black**)

Motherboard

Super X11DPU

Processor

CPU ■ Dual Socket P (LGA 3647)
 ■ 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors[‡],
 Dual UPI up to 10.4GT/s
 ■ Support CPU TDP 70-205W

Cores ■ Up to 28 Cores

Note [‡] BIOS version 3.2 or above is required to support 2nd Gen Intel® Xeon® Scalable processors (codenamed Cascade Lake-R)

System Memory

Memory Capacity ■ 24 DIMM slots
 ■ Up to 6TB 3DS ECC DDR4-2933MHz[†] RDIMM/LRDIMM
 ■ Supports Intel® Optane™ DCPMM^{††}

Memory Type ■ 2933[†]/2666/2400/2133MHz ECC DDR4 RDIMM/LRDIMM
 ■ 2666 ECC DDR4 NVDIMM

Note [†] 2933MHz in two DIMMs per channel can be achieved by using memory purchased from Supermicro
^{††} Cascade Lake only. Contact your Supermicro sales rep for more info.

On-Board Devices

Chipset ■ Intel® C621 chipset

SATA ■ SATA3 (6Gbps) with RAID 0, 1, 5, 10

Network Connectivity ■ 4x 10GBase-T ports via AOC-2UR66-i4XTF (Intel® XL710-BM1 + X557-AT4)

IPMI ■ Support for Intelligent Platform Management Interface v.2.0
 ■ IPMI 2.0 with virtual media over LAN and KVM-over-LAN support

Graphics ■ ASPEED AST2500 BMC

Input / Output

SATA ■ 12 SATA3 (6Gbps) ports

SAS ■ 8 SAS3 + 4 SAS3/NVMe support optional

LAN ■ 4 RJ45 10GBase-T Ethernet LAN ports
 ■ 1 RJ45 Dedicated IPMI LAN port

USB ■ 3 USB 3.0 ports (2 rear, 1 Type A)

Video ■ 2 VGA ports (1 rear, 1 onboard)

Serial Port / Header ■ 1 Serial header

DOM ■ 2 SuperDOM (Disk on Module) ports

Chassis

Form Factor ■ 2U Rackmount

Model ■ **CSE-829U2TS-R1K02P-T**

Dimensions and Weight

Width ■ 17.2" (437mm)

Height ■ 3.5" (89mm)

Depth ■ 28.46" (723mm)

Weight ■ Net Weight: 36 lbs (16.4 kg)
 ■ Gross Weight: 72 lbs (32.7 kg)

Available Colors ■ Black

Front Panel

Buttons ■ Power On/Off button
 ■ System Reset button

LEDs ■ Power status LED
 ■ HDD activity LED
 ■ Network activity LEDs
 ■ System information (overheat/UID) LED

Expansion Slots

PCI-Express ■ 2 PCI-E 3.0 x16 (FH, 10.5" L)
 ■ 4 PCI-E 3.0 x8 (FH, 10.5" L)
 ■ 1 PCI-E 3.0 x8 (LP)

(Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and [AOC Support](#) for details.)

Drive Bays / Storage

Hot-swap ■ 12 Hot-swap 3.5" drive bays
 ■ 12 SATA3 ports by default;
 Optional 8 SAS3 + 4 NVMe/SAS3

M.2 ■ 1 M.2 PCI-E 3.0 x4 M-Key NVMe or 1 M.2 M-Key SATA3 (2240/2260/2280/22110) via optional riser card (see optional parts list)
 ■ 2 M.2 PCI-E 3.0 x4 M-Key NVMe (2260/2280/22110) via optional add-on card AOC-SLG3-2M2

Backplane

2U SAS/SATA backplane

System Cooling

Fans ■ 4 Heavy duty 8cm PWM fans

Power Supply

1000W Redundant Power Supplies with PMBus

Total Output Power ■ 800W: 100 – 127Vac
 ■ 1000W: 200 – 240Vac
 ■ 1000W: 200 – 240Vdc (for CCC only)

Dimension (W x H x L) ■ 73.5 x 40 x 203 mm

System BIOS

- | | |
|------------------|--|
| BIOS Type | <ul style="list-style-type: none"> AMI 32Mb SPI Flash ROM |
|------------------|--|

Management

- | | |
|-----------------|---|
| Software | <ul style="list-style-type: none"> Intel® Node Manager IPMI 2.0 KVM with dedicated LAN NMI SSM, SPM, SUM SuperDoctor® 5 |
|-----------------|---|

- | | |
|-----------------------------|---|
| Power Configurations | <ul style="list-style-type: none"> ACPI Power Management |
|-----------------------------|---|

PC Health Monitoring

- | | |
|------------|--|
| CPU | <ul style="list-style-type: none"> Monitors for CPU Cores, Chipset Voltages, Memory. 4+1 Phase-switching voltage regulator |
|------------|--|

- | | |
|------------|---|
| FAN | <ul style="list-style-type: none"> Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors |
|------------|---|

- | | |
|--------------------|--|
| Temperature | <ul style="list-style-type: none"> Monitoring for CPU and chassis environment Thermal Control for fan connectors |
|--------------------|--|

- | | |
|--------------|--|
| Input | <ul style="list-style-type: none"> 100-127Vac / 9.8 - 7A / 50-60Hz 200-240Vac / 7 - 5A / 50-60Hz 200-240Vdc / 7 - 5A (for CCC only) |
|--------------|--|

- | | |
|-------------|---|
| +12V | <ul style="list-style-type: none"> Max: 66.7A / Min: 0A (100-127Vac) Max: 83A / Min: 0A (200-240Vac) Max: 83A / Min: 0A (200-240Vdc) |
|-------------|---|

- | | |
|--------------|---|
| 12Vsb | <ul style="list-style-type: none"> Max: 2.1A / Min: 0A |
|--------------|---|

- | | |
|--------------------|--|
| Output Type | <ul style="list-style-type: none"> 25 Pairs Gold Finger Connector |
|--------------------|--|

- | | |
|----------------------|---|
| Certification |   Titanium Level
[Test Report] |
|----------------------|---|

Operating Environment

- | | |
|-------------|--|
| RoHS | <ul style="list-style-type: none"> RoHS Compliant |
|-------------|--|

- | | |
|----------------------------|---|
| Environmental Spec. | <ul style="list-style-type: none"> Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing) |
|----------------------------|---|

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11DPU	1	Super X11DPU Motherboard
	CSE-829U2TS-R1K02P-T	1	2U Chassis
Add-on Card / Module	AOC-2UR66-I4XTF-P	1	2U Ultra Riser 4-port 10GBase-T, Intel XL710-BM1 and X557-AT4
Backplane	BPN-SAS3-826A-N4	1	12-port 2U SAS3 12Gbps hybrid backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x SAS3/SATA3/NVMe Storage Devices
Cable 1	CBL-PWEX-0652	1	8 pin female to 2x RA(Right Angle) big 4 pin female power, 60/65CM, 18AWG,RoHS/REACH
Cable 2	CBL-PWEX-0673	1	8 pin female to 2x big 4 pin female power, 65/70CM, 18AWG,RoHS/REACH
Cable 3	CBL-SAST-0655	1	MINI SAS HD(ST)-MINI SAS(RA-RS EXIT),6G,INT,47CM,SB,30AWG
Cable 4	CBL-SAST-0656	1	MINI SAS HD(ST)-MINI SAS(RA-RS EXIT),6G,INT,39CM,SB,30AWG
Cable 5	CBL-SAST-0657	1	MINI SAS HD(ST)-MINI SAS(RA-RS EXIT),6G,INT,55CM,SB,30AWG
Air Shroud	MCP-310-82921-0N	1	Plastic air shroud for SC829U, 219U (X11 24DIMM, left side)
Air Shroud	MCP-310-82922-0N	1	Plastic air shroud for SC829U, 219U (X11 24DIMM, right side)
Riser Card	RSC-R1UW-E8R	1	1U RHS WIO Riser card with one PCI-E x8 slot
Riser Card	RSC-R2UW-4E8	1	2U LHS WIO Riser card with four PCI-E x4 slots
Heatsink / Retention	SNK-P0068PS	2	2U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
* Power Supply	PWS-1K02A-1R	2	1U 1000W Redundant Power Supply 73.5mm width Titanium Level,RoHS/REACH
* Cable 6	CBL-0088L	4	4 PIN MIDDLE FAN POWER CABLE (PWM). 27cm, 24AWG
* Cable 7	CBL-0160L	2	NEMA5-15P to C13 US power cord 16AWG 6ft, PBF (default for high watt)
* Cable 8	CBL-0318L	1	CBL,FRONT CNTL,16 TO 16 PIN,RA,RND TUBE,24CM,28AWG
* FAN 1	FAN-0118L4	4	80 x 80 x 38 mm, 9.5K RPM, 4-pin PWM Fan, Hot
* Parts	MCP-150-00009-0B	1	Internal AOC rubber support for SC819U, 119U
* Drive Tray(s)	MCP-220-00075-0B	12	Black gen 5.5 hot-swap 3.5"; HDD tray
* Rail Set	MCP-290-00057-0N	1	Rail set, quick/quick, default for 4U 17.2"; W
* Rail Set	MCP-290-00060-0N	1	Threaded rail adapter default for round hole rack
* Air Shroud	MCP-310-81905-0B	1	Plastic air shroud for SC819U, 119U, 829U, 219U (PWS),RoHS/REACH
* Front Panel	TB826	1	Front panel adaptor board (TB826) forSC826,213,216,219
* Rail Set	MCP-290-00115-0N	1	Inner rail, quick-release type
* Rail Set	MCP-290-00117-0N	1	Outer rail, quick-release type

Notes:

- Parts with * are inside the chassis
- Excessive parts might not be shipped, including but not limited to excessive drive trays, fans, riser brackets, air shrouds, IO shields, cables.....etc.

Optional Parts List

	Part Number	Qty	Description
Add-on card for internal M.2 NVMe	AOC-SLG3-2M2	1	Low Profile PCI-E x8 add-on card supports 2 PCI-E 3.0 x4 M-Key M.2 NVMe Modules
2U Cable Management Arm	MCP-290-00128-0N & MCP-290-00127-0N	1	2U Supermicro Cable Management Arm 2nd Gen (Compatible for racks that are 42" in depth)

Internal Drive Tray for Two 2.5" Drives	MCP-120-82916-0N	1	Internal drive plate Supports Two 2.5" Drive, PCI slots
	CBL-PWEX-0650	1	Power cable for Two internal 2.5" drives
	CBL-0080L	2	
	CBL-0484L Or CBL-SAST-0654 Or	2 1	SATA3 S-S Cable miniSAS(iPass) to 4 SATA Cable
	CBL-SAST-0948	1	miniSAS HD to 4 SATA Cable
Cable for 4 NVMe Hybrid Drive Bays	2 CBL-SAST-0929 & 2 CBL-SAST-0972	1	OCuLink source to MiniSAS HD target V.91,INT,PCIe NVMe SSD, 57CM,34AWG
Hot-swap 3.5" to 2.5" NVMe Drive Tray	MCP-220-00138-0B	1~4	Tool-less black hot-swap 3.5-to-2.5 converter NVMe drive tray (Orange tab)
Hot-swap 3.5" to 2.5" SATA/SAS Drive Trays	MCP-220-00118-0B	1~12	Tool-less black hot-swap 3.5-to-2.5 converter HDD drive tray (Red tab)
	MCP-220-00043-0N		Black hot-swap 3.5-to-2.5 converter HDD drive tray (Red tab)
2 Internal M.2 slots (1 SATA, 1 NVMe)	RSC-UMR-8 & CBL-SAST-0538 & MCP-120-82924-0N & MCP-310-21902-0N	1	1U Ultra RHS Riser Card with 1 PCIE/SATA Hybrid M.2 & 1 PCIE X8
2 Rear 2.5" Hot-swap SATA Drive Bays (Complete System Only)	MCP-240-82922-0N-OEM	-	Rear 2x 2.5" HDDs riser bracket kit for SC829U/219U, tool-less
Storage Control Card and Cable(s)	AOC-S3008L-L8e & 2x CBL-SAST-0531	1~2	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 122HDD, HBA; MINI SAS HD,12G,INT,60CM,30AWG
	AOC-S3008L-L8i & 2x CBL-SAST-0531		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 63HDD, RAID 0,1,1E; MINI SAS HD,12G,INT,60CM,30AWG
	AOC-S3108L-H8iR & 2x CBL-SAST-0531		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60; MINI SAS HD,12G,INT,60CM,30AWG
	AOC-S3108L-H8iR-16DD & 2x CBL-SAST-0531		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 16HDD, RAID 0, 1, 5, 6, 10, 50, 60; MINI SAS HD,12G,INT,60CM,30AWG
Network Card(s)	AOC-SGP-i2/4	-	Standard LP, 2/4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STGN-i1S/i2S	-	Standard LP, 1/2x 10GbE SFP+, PCI-E x8, Intel 82599EN
	AOC-STGF-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel XL710-BM2
	AOC-STG-i4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Intel XL710
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X540
	AOC-STGS-i1/2T	-	Standard LP, 1/2x 10GbE RJ45, PCI-E x8, Intel X550
	AOC-STG-i4T	-	Standard LP, 4x 10GbE RJ45, PCI-E x8, Intel XL710
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel 82598EB
	AOC-S25G-m2S	-	Standard LP, 2x 25GbE SFP28, Mellanox ConnectX-4 LX EN
	AOC-S40G-i2Q	-	Standard LP 2-port 40GbE controller, Intel Fortville XL710
	More	-	AOC Compatibility Matrix
	CacheVault(s)	BTR-CV3108-U1	-
Hot-swap 3.5" to 2.5" Hard Disk Drive Tray	MCP-220-00043-0N	-	Black hot-swap 3.5" to 2.5" HDD tray
TPM security module	AOM-TPM-9670H-S	1	TCG 2.0 compliant trusted platform module (TPM), Horizontal FF
	AOM-TPM-9671H-S	1	TCG 1.2 compliant trusted platform module (TPM), Horizontal FF
Intel VROC RAID Key	AOC-VROCINTMOD	1	Intel VROC, RAID 0, 1, 5, 10 (Intel SSD Only)
	AOC-VROCSTNMOD	1	Intel VROC Standard, RAID 0, 1, 10
	AOC-VROCPREMOD	1	Intel VROC Premium, RAID 0, 1, 5, 10
Global Services & Support	OS4HR3/2/1	-	3/2/1-year onsite 24x7x4 service
	OSNBD3/2/1	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC • eStore	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)