

# DH-SD8A440WA-HNF

## 4MP 40x Starlight+ IR WizMind Network PTZ Camera




- 1/1.8" CMOS
- Powerful 40x optical zoom
- Starlight+ technology
- IR distance up to 500 m
- Support face recognition
- Deep-learning-based auto tracking and perimeter protection
- Support metadata
- Support Hi-PoE
- Smart wiper
- IP67



Launched by Dahua Technology, Dahua WizMind is a full portfolio of solutions composed of project-oriented products including IPC, NVR, PTZ, XVR, Thermal and software platform which adopts industry-leading deep learning algorithms. Focusing on customer's requirements, WizMind provides precise, reliable and comprehensive AI solutions for industry verticals.

### System Overview

Dahua PTZ AI network camera adopts advanced CNN deep learning algorithms to support face recognition with high accuracy. This camera possess wide monitor range, PFA algorithm that can always present a clear, focused image while zooming, and smart wiper technology that supported by RainSensor.

### Functions

#### Starlight+ Technology

For challenging low-light applications, Dahua's Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing color details in low light down to 0.001 Lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

#### Face Recognition

Once facial features are extracted from captured faces, they are stored in a database where they can be easily searched and compared against other images. Once a successful match is found, the system outputs the result. The Dahua Face Recognition camera supports a built-in database that stores up to 10,000 facial images, helping the camera achieve real-time face capture and comparison.

#### Perimeter Protection

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improves alarm accuracy.

#### Metadata

Metadata is feature attribute information extracted from a target object which can be used for data retrieval. There are four kinds of metadata supported by Dahua PTZ AI camera: human face, human body, motor vehicle and non-motor vehicle metadata. Facial information includes gender, age, glasses, masks, beards, etc. Human body information includes hat, top, top color, bottom, bottom color, bag, etc. Motor vehicle information includes plate color, type, vehicle color, sunshield, ornament, calling, seatbelt, smoking, annual inspection sticker, etc. Non-motor vehicle information includes type, color, top type, top color, people number, etc.

#### PFA Technology

PFA technology has innovatively introduced new methods of judgment to ensure the accuracy and predictability of the direction of subject distance adjustment. The result is a set of advanced focusing algorithms. PFA ensures clarity of the image throughout the process of zooming and shortens focus time. The realization of PFA technology substantially improves user experience and increases product value.

#### Environment

Dahua cameras operate in extreme temperature environments, rated for use in temperatures from -40 °C to +70 °C (-40 °F to +158 °F) with 95% humidity. Subjected to rigorous dust and water immersion tests and certified to the IP67 Ingress Protection rating make it suitable for demanding outdoor applications.

#### Protection

The camera allows for ±25% input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 8KV lightning rating provides effective protection for both the camera and its structure against lightning.

#### Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

**Technical Specification**
**Camera**

Image Sensor	1/1.8" CMOS
Pixel	4MP
Max. Resolution	2560 (H) x 1440 (V)
Electronic Shutter Speed	1/1 s–1/30,000 s
Scanning System	Progressive
Min. Illumination	Color: 0.001 Lux@F1.4 B/W: 0.0001 Lux@F1.4 0 Lux@F1.4 (illuminator on)
Illumination Distance	500 m (1640.42 ft)
Illumination On/Off Control	Auto; Manual
Illuminator Number	10
Wiper	Smart wiper

**Lens**

Focal Length	5.6 mm–223 mm			
Max. Aperture	F1.4– F4.8			
Field of View	H: 63.9°–2.0°; V: 36°–1.3°; D: 68.18°–2.62°			
Optical Zoom	40x			
Focus Control	Auto; Manual			
Close Focus Distance	0.1 m–1 m (0.33 ft–3.28 ft)			
Iris Control	Auto			
DORI Distance	Detect	Observe	Recognize	Identify
	3030 m (9940.94 ft)	1204 m (3950.13 ft)	606 m (1988.19 ft)	303 m (994.09 ft)

**PTZ**

Pan/Tilt Range	Pan: 0°–360° endless Tilt: -30°–90°, auto flip 180°
Manual Control Speed	Pan: 0.1°–240°/s Tilt: 0.1°–100°/s
Preset Speed	Pan: 240°/s; Tilt: 120°/s
Preset	300
Tour	8 (up to 32 presets per tour)
Pattern	5
Scan	5
Speed Adjustment	Yes
Power-off Memory	Yes
Idle Motion	Preset; Tour; Pattern; Scanning
Protocol	DH-SD; Pelco-P/D (auto recognition)

**General Intelligence**

Event Trigger	Motion detection; video tampering; scene changing; network disconnection; IP address conflict; illegal access; storage anomaly
---------------	--

IVS	Object abandoned; object missing
-----	----------------------------------

**Artificial Intelligence**

Auto Tracking	Yes
Face Recognition	Yes
Perimeter Protection	Tripwire and intrusion. Support alarm triggering by target types (human and vehicle). Support filtering false alarms caused by animals, rustling leaves, bright lights, etc.
Video Metadata	Support human body, human face, motor vehicle and non-motor vehicle image capture and attributes extraction.

**Video**

Compression	Smart H.265+; H.265; Smart H.264+; H.264; MJPEG (Sub Stream 1)
Streaming Capability	3 streams
Resolution	4M (2560 x 1440)/3M (2048 x 1536)/1080P (1920 x 1080)/1.3M (1280 x 960)/720P (1280 x 720)/ D1 (704 x 576/704 x 480)/CIF (352 x 288/352 x 240)
Frame Rate	Main stream: 4M/3M/1080P/1.3M/720P (1 fps–25/30 fps) Sub stream1: D1/CIF(1 fps–25/30 fps) Sub stream2: 1080P/1.3M/720P (1 fps–25/30 fps)
Bit Rate Control	Variable; Constant
Bit Rate	H.265/H.264: 512 Kbps–8192 Kbps
Day/Night	Auto (ICR); Color; B/W
BLC	Yes
WDR	120 dB
HLC	Yes
White Balance	Auto; ATW; Indoor; Outdoor; Manual
Gain Control	Auto; Manual
Noise Reduction	Ultra DNR (2D/3D)
Motion Detection	Yes
Region of Interest (RoI)	Yes
Image Stabilization	Electronic (EIS)
Defog	Optical
Digital Zoom	16x
Flip	180°
Privacy Masking	Up to 24 areas

**Audio**

Compression	G.711a; G.711mu; PCM; G.726; AAC; G722.1; G.729; MPEG2-Layer2
-------------	---

**Network**

Ethernet	RJ-45 (10Base-T/100Base-TX)
Protocol	IPv4/IPv6; HTTP; HTTPS; SSL; TCP/IP; UDP; UPnP; ICMP; IGMP; SNMP v1/v2c/v3 (MIB-2); ARP; RTCP; RTSP; RTP; SMTP; NTP; DHCP; DNS; PPPoE; DDNS; FTP; IP Filter; QoS; Bonjour; 802.1x; RTMP

Interoperability	ONVIF Profile S&G&T; API
Streaming Method	Unicast; Multicast
User/Host	20 (total bandwidth 64 MB)
Storage	NAS (Network Attached Storage); local PC for instant recording; Micro SD card (256 GB)
Browser	IE; Chrome; Firefox; Safari
Management Software	Smart PSS; DSS; DMSS
Mobile Phone	IOS; Android

**Certification**

Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB,ANSI C63.4-2014
----------------	---

**Port**

Analog Output	1 port (BNC, 1.0V[p-p], 75Ω)
RS485	1
Audio I/O	1/1
Alarm I/O	7/2

**Power**

Power Supply	DC 36V/2.23A (±25%); Hi-PoE
Power Consumption	26W, 42W (heater on, IR on)

**Environment**

Operating Temperature	-40°C to +70°C (-40°F to +158°F)
Operating Temperature	Less than 95% RH
Protection	IP67

**Structure**

Casing	Metal
Dimensions	Φ262 mm × 415.6 mm (Φ10.31" × 16.36")
Net Weight	8.5 kg (18.74 lb)
Gross Weight	13.5 kg (29.76 lb)

**Ordering Information**

Type	Part Number	Description
4MP WizMind PTZ Camera	DH-SD8A440WA-HNF	4MP 40x Starlight IR WizMind AI Network PTZ Camera, WDR, PAL
	DH-SD8A440WAN-HNF	4MP 40x Starlight IR WizMind AI Network PTZ Camera, WDR, NTSC
	SD8A440WA-HNF	4MP 40x Starlight IR WizMind AI Network PTZ Camera, WDR, PAL
	SD8A440WAN-HNF	4MP 40x Starlight IR WizMind AI Network PTZ Camera, WDR, NTSC

Accessories	PFB306W	Wall Mount Bracket
	DC 36V/2.23A	Power Adapter
	PFA118	Mount Adapter
	PFB710C	Ceiling Mount Bracket
	PFA150	Pole Mount Bracket
	PFB301S-E	Plane Mount Bracket

**Accessories**

Included:



PFB306W  
Wall Mount Bracket



DC 36V/2.23A  
Power Adapter

Optional:



PFA118  
Mount Adapter



PFB710C  
Ceiling Mount Bracket



PFA150  
Pole Mount Bracket



PFB301S-E  
Plane Mount Bracket

Wall Mount	Ceiling Mount
PFB306W	PFA118+PFB710C
Pole Mount	Plane Mount
PFB306W+PFA150	PFB301S-E

**Dimensions (mm)**

