

Storage A+ Server ASG-1115S-NE316R (Complete System Only

Datasheet Share

1U front-loading all-flash storage server with 16 E3.S NVMe drives and PCIe 5.0



Key Applications

- Software-defined Storage
- Data Intensive HPC
- NVMe Over Fabrics Solution
- In-Memory Computing
- Private & Hybrid Cloud

Key Features

1. Single Socket SP5 AMD EPYC™ 9004/9005 Series processor; up to 300W TDP
2. Supports 24 DIMMs with 2DPC, up to 9TB memory capacity with 24 DIMMs of 384GB 3DS RDIMM/RDIMM DDR5 ECC memory
3. 2 PCIe 5.0 x16 slots & 2 AIOM connectors (OCP 3.0 SFF compliant)
4. 16 Hot-swap E3.S (7.5mm) NVMe drive bays
5. Redundant Titanium 1600W Power Supplies

...

[Get Pricing](#)

[Contact Us](#)
Compare

Specifications Resources & Downloads Parts List

Product SKUs

A+ Server **ASG-1115S-NE316R**

Motherboard

Super H13SSF

Processor

CPU Single processor(s)
[AMD EPYC™ 9004/9005 Series Processors](#)
(* AMD EPYC™ 9005 Series drop-in support requires board revision 2.x)

Core Count Up to 96C/192T

Note Supports 200W - 300W TDP CPUs
* This system supports AMD EPYC™ 9004/9005 Series processors up to 400W TDP

System Memory

Memory Slot Count: 24 DIMM slots
Max Memory (1DPC): Up to 3TB 4800MT/s ECC DDR5 RDIMM (AMD EPYC™ 9004 Series Processor)
Max Memory (2DPC): Up to 6TB 4000MT/s ECC DDR5 RDIMM (AMD EPYC™ 9004 Series Processor)
Max Memory (1DPC): Up to 4.5TB 5200MT/s ECC DDR5 RDIMM (AMD EPYC™ 9005 Series Processor)
Max Memory (2DPC): Up to 9TB 4400MT/s ECC DDR5 RDIMM (AMD EPYC™ 9005 Series Processor)
[View Memory Options >](#)

Memory Voltage 1.1V

On-Board Devices

Chipset AMD System on Chip

Network Connectivity Via AIOM
[View AIOM Options >](#)
[View AOC Options >](#)

Input / Output

LAN 1 RJ45 1 GbE Dedicated BMC LAN port

USB 2 USB 3.0 ports(rear)
2 USB 3.0 ports(front)

Video 1 VGA port

System BIOS

BIOS Type AMI 32MB SPI Flash EEPROM

Management

Software [SuperCloud Composer](#)
[Supermicro Server Manager \(SSM\)](#)
[Supermicro Update Manager \(SUM\)](#)
[Supermicro SuperDoctor® 5 \(SD5\)](#)
[Super Diagnostics Offline \(SDO\)](#)
[Supermicro Thin-Agent Service \(TAS\)](#)
[SuperServer Automation Assistant \(SAA\) New!](#)

Power configurations Power-on mode for AC power recovery
ACPI Power Management

Security

Hardware Trusted Platform Module (TPM) 2.0
Silicon Root of Trust (RoT) – NIST 800-193 Compliant

Features Cryptographically Signed Firmware
Secure Boot
Secure Firmware Updates
Automatic Firmware Recovery
Supply Chain Security: Remote Attestation
Runtime BMC Protections
System Lockdown

PC Health Monitoring

CPU Monitors for CPU Cores, Chipset Voltages, Memory
4+1 Phase-switching voltage regulator

FAN Fans with tachometer monitoring
Status monitor for speed control
Pulse Width Modulated (PWM) fan connectors

Temperature Monitoring for CPU and chassis environment
Thermal Control for fan connectors

Voltage +1.8V, +12V, +3.3V, +5V, +5V standby, 10 -fan status, 3.3V standby, HT, Memory, VBAT

Chassis

Form Factor 1U Rackmount

Model **CSE-126E32-R1K62P**

Dimensions and Weight

Height 1.7" (43.6 mm)

Width 17.2" (438.4 mm)

Depth 30.4" (773.25 mm)

Package 7.87" (H) x 23.81" (W) x 40.55" (D)

Weight Gross Weight: 68.74 lbs (31.2 kg)
Net Weight: 48 lbs (21.8 kg)

Available Color Silver

Front Panel

LED Network activity
Power status
SSD activity
System information (overheat/UID)

Buttons Power On/Off

Expansion Slots

PCI-Express (PCIe) Configuration Default
2 PCIe 5.0 x16 FHHL slots
2 PCIe 5.0 x16 AIOM slots (OCP 3.0 compatible)
[View AOC Options >](#)

M.2 2 M.2 PCIe 3.0 x2 NVMe slots (M-key 2280/22110)

Drive Bays / Storage

Drive Bays Configuration Default: Total 16 bays
16 front hot-swap E3.S 1T PCIe 5.0 x4 NVMe drive bays
[View NVMe Options >](#)

M.2 1 M.2 PCIe 3.0 x2 NVMe slot (M-key 2280/22110)
1 M.2 PCIe 3.0 x4 NVMe slot (M-key 2280/22110)
[View M.2 Options >](#)

System Cooling

Fans 8 Heavy Duty 4cm Fan(s)

Power Supply

1x 1600W Redundant Titanium Level (96%) power supply

Dimension (WxHxL) 73.5 x 40 x 203 mm

Input 1000W: 100-127Vac
1000W: 100-127Vac / 50-60Hz
1600W: 200-240Vac
1600W: 200-240Vac / 50-60Hz

+12V Max: 83.3A / Min: 0A (100Vac-127Vac)
Max: 83A / Min: 0A (100Vac-127Vac)
Max: 133A / Min: 0A (200Vac-240Vac)

12V SB Max: 2.1A / Min: 0A

Output Type Backplanes (gold finger)

Certification **Titanium Level**
[[Test Report](#)]

Operating Environment

ROHS RoHS Compliant

Environmental Spec. Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F)
Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)
Operating Relative Humidity: 8% to 90% (Non-condensing)
Non-operating Relative Humidity: 8% to 95% (Non-condensing)

Environmental / Recycling

Recycle [Return Server-End of Life Product](#)

Certain products may not be available in your region

Global SKU **English**

About Us

- Company Profile
- Green Computing
- Investor Relations
- Careers
- Site Map
- Glossary

News

- Press Releases
- Supermicro in the News
- Product Reviews
- Events
- Webinars

Resources

- Product Briefs
- Solution Briefs
- Success Stories
- Videos
- White Papers
- Thought Leadership
- MySupermicro
- Data Center Stories

Connect & Follow

- Locations
- Contact Us
- Newsletter Sign-up

