

SuperServer 2029U-E1CR25M (Complete System Only)



Integrated Board



Super X11DPU

Views: | [Angled View](#) | [Top View](#) |
| [Front View](#) | [Rear View](#) |

Complete System Only: To maintain quality and integrity, this product is sold only as a completely-assembled system (with minimum 2 CPUs, 4 DIMMs and a storage add-on-card).

[▶ Drivers & Utilities](#) | [▶ BIOS](#) | [▶ IPMI](#) | [▶ Tested Memory](#) | [▶ Tested M.2 List](#) | [▶ NVMe Options](#) | [▶ Manuals](#) | [▶ OS Certification Matrix](#)
[▶ Compatible GPU List](#) | [▶ Quick-References Guide](#) | [▶ Drive Options](#) | [▶ Network Card \(AOC\) Matrix](#)

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Key Features

Virtualization
Hyperconverge Storage
Cloud Computing
High End Enterprise Server

1. Dual Socket P (LGA 3647) support 2nd Gen Intel® Xeon® Scalable processors (Cascade Lake/Skylake)[‡]
2. 24 DIMMs; up to 6TB 3DS ECC DDR4-2933MHz[†] RDIMM/LRDIMM, Supports Intel® Optane™ DCPMM^{††}
3. 1 PCI-E 3.0 x16 slot (FH, 10.5" L), 5 PCI-E 3.0 x8 slots (FH, 10.5" L), 1 PCI-E 3.0 x8 slot (LP), 1 PCI-E 3.0 x8 slot (internal LP)
4. 2 25GbE SFP28 Ethernet ports
5. 24 Hot-swap 2.5" drive bays: 24 SAS3 via opt. AOC (4 hybrid ports - opt. 4 NVMe), Optional 2 hot-swap 2.5" rear drive bays for SSDs; Optional M.2 NVMe and SATA3 ports
6. 4 Heavy duty 8cm PWM fans
7. 1000W Redundant Power Supplies **Titanium Level (96%)**

Specifications

Product SKUs

SYS-2029U-E1CR25M	<ul style="list-style-type: none"> SuperServer 2029U-E1CR25M (Black)
--------------------------	---

Motherboard

Super X11DPU

Processor

CPU	<ul style="list-style-type: none"> Dual Socket P (LGA 3647) 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors[‡], Dual UPI up to 10.4GT/s Support CPU TDP 70-205W
------------	---

Cores	<ul style="list-style-type: none"> Up to 28 Cores
--------------	--

Note	<ul style="list-style-type: none"> [‡] BIOS version 3.2 or above is required to support 2nd Gen Intel® Xeon® Scalable processors (codenamed Cascade Lake-R)
-------------	---

System Memory

Memory Capacity	<ul style="list-style-type: none"> 24 DIMM slots Up to 6TB 3DS ECC DDR4-2933MHz[†] RDIMM/LRDIMM Supports Intel® Optane™ DCPMM^{††}
------------------------	--

Memory Type	<ul style="list-style-type: none"> 2933[†]/2666/2400/2133MHz ECC DDR4 RDIMM/LRDIMM 2666 ECC DDR4 NVDIMM
--------------------	--

Note	<ul style="list-style-type: none"> [†] 2933MHz in two DIMMs per channel can be achieved by using memory purchased from Supermicro ^{††} Cascade Lake only. Contact your Supermicro sales rep for more info.
-------------	--

On-Board Devices

Chipset	<ul style="list-style-type: none"> Intel® C621 chipset
----------------	---

SAS	<ul style="list-style-type: none"> SAS3 (12Gbps) via expander + Broadcom 3108/3008 AOC
------------	---

Network Connectivity	<ul style="list-style-type: none"> 2 25GbE SFP28 ports via AOC-2UR68-m2TS (Mellanox ConnectX-4 Lx EN)
-----------------------------	--

IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
-------------	--

Graphics	<ul style="list-style-type: none"> ASPEED AST2500 BMC
-----------------	--

Input / Output

SAS	<ul style="list-style-type: none"> 24 SAS3 ports support via expander and storage Add-on Cards
------------	---

LAN	<ul style="list-style-type: none"> 2 25GbE SFP28 ports 1 RJ45 Dedicated IPMI LAN port
------------	---

USB	<ul style="list-style-type: none"> 3 USB 3.0 ports (2 rear, 1 Type A)
------------	--

Video	<ul style="list-style-type: none"> 1 VGA Connector
--------------	---

Serial Header	<ul style="list-style-type: none"> 1 Serial header
----------------------	---

DOM	<ul style="list-style-type: none"> 2 SuperDOM (Disk on Module) ports
------------	---

Chassis

Form Factor	<ul style="list-style-type: none"> 2U Rackmount
--------------------	--

Model	<ul style="list-style-type: none"> CSE-219U2TS-R1K02P-T
--------------	--

Dimensions and Weight

Width	<ul style="list-style-type: none"> 17.2" (437mm)
--------------	---

Height	<ul style="list-style-type: none"> 3.5" (89mm)
---------------	---

Depth	<ul style="list-style-type: none"> 27.76" (705.3mm)
--------------	--

Weight	<ul style="list-style-type: none"> Net Weight: 36 lbs (16.4 kg) Gross Weight: 72 lbs (32.7 kg)
---------------	--

Available Colors	<ul style="list-style-type: none"> Black
-------------------------	---

Front Panel

Buttons	<ul style="list-style-type: none"> Power On/Off button System Reset button
----------------	--

LEDs	<ul style="list-style-type: none"> Power status LED HDD activity LED Network activity LEDs System information (overheat/UID) LED
-------------	--

Expansion Slots

PCI-Express	<ul style="list-style-type: none"> 1 PCI-E 3.0 x16 (FH, 10.5" L) 5 PCI-E 3.0 x8 (FH, 10.5" L) 1 PCI-E 3.0 x8 (LP) 1 PCI-E 3.0 x8 (internal LP)
--------------------	--

(Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and [AOC Support](#) for details.)

Drive Bays / Storage

Hot-swap	<ul style="list-style-type: none"> 24 Hot-swap 2.5" drive bays: 24 SAS3 via opt. AOC (4 hybrid ports - opt. 4 NVMe)
-----------------	--

Note: Storage Add-on card is required

M.2	<ul style="list-style-type: none"> 1 M.2 PCI-E 3.0 x4 M-Key NVMe or 1 M.2 M-Key SATA3 (2240/2260/2280/22110) via optional riser card (see optional parts list) 2 M.2 PCI-E 3.0 x4 M-Key NVMe (2260/2280/22110) via optional add-on card AOC-SLG3-2M2
------------	--

System Cooling

Fans	<ul style="list-style-type: none"> 4 Heavy duty 8cm PWM fans
-------------	---

Shroud	<ul style="list-style-type: none"> 1 Air Shroud
---------------	--

Power Supply

1000W Redundant Power Supplies with PMBus

Total Output Power	<ul style="list-style-type: none"> 800W: 100 – 127Vac 1000W: 200 – 240Vac 1000W: 200 – 240Vdc (for CCC only)
---------------------------	---

System BIOS

- BIOS Type** ■ AMI 32Mb SPI Flash ROM

Management

- Software** ■ Intel® Node Manager
 ■ [Redfish API](#)
 ■ [IPMI 2.0](#)
 ■ KVM with dedicated LAN
 ■ NMI
 ■ [SSM](#), [SPM](#), [SUM](#)
 ■ [SuperDoctor® 5](#)

- Power Configurations** ■ ACPI Power Management

PC Health Monitoring

- CPU** ■ Monitors for CPU Cores, Chipset Voltages, Memory.
 ■ 4+1 Phase-switching voltage regulator

- FAN** ■ Fans with tachometer monitoring
 ■ Status monitor for speed control
 ■ Pulse Width Modulated (PWM) fan connectors

- Temperature** ■ Monitoring for CPU and chassis environment
 ■ Thermal Control for fan connectors

- Dimension (W x H x L)** ■ 73.5 x 40 x 203 mm

- Input** ■ 100-127Vac / 9.8 - 7A / 50-60Hz
 ■ 200-240Vac / 7 - 5A / 50-60Hz
 ■ 200-240Vdc / 7 - 5A (for CCC only)

- +12V** ■ Max: 66.7A / Min: 0A (100-127Vac)
 ■ Max: 83A / Min: 0A (200-240Vac)
 ■ Max: 83A / Min: 0A (200-240Vdc)

- 12Vsb** ■ Max: 2.1A / Min: 0A

- Output Type** ■ 25 Pairs Gold Finger Connector

- Certification** ■   **Titanium Level [Test Report]**

Operating Environment

- RoHS** ■ RoHS Compliant

- Environmental Spec.** ■ Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F)
 ■ Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)
 ■ Operating Relative Humidity: 8% to 90% (non-condensing)
 ■ Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11DPU	1	Super X11DPU Motherboard
	CSE-219U2TS-R1K02P-T	1	2U Chassis
Add-on Card / Module	AOC-2UR68-M2TS-O	1	[NR]AOC-2UR68-M2TS-P
Backplane	BPN-SAS3-216EL1-N4	1	24-port 2U SAS3 12Gbps single-expander backplane, support up to 20x 2.5-inch SAS3/SATA3 HDD/SSD and 4x NVMe/SAS3/SATA3 storage devices
Cable 1	CBL-PWEX-0673	3	8 pin female to 2x big 4 pin female power, 65/70CM, 18AWG,RoHS/REACH
Cable 2	CBL-SAST-0593	2	MINI SAS HD,12G,INT,60CM,30AWG
Parts	MCP-240-82914-0N	1	Ultra I/O bracket for SC829U, 219U (B2TS)
Air Shroud	MCP-310-82921-0N	1	Plastic air shroud for SC829U, 219U (X11 24DIMM, left side)
Air Shroud	MCP-310-82922-0N	1	Plastic air shroud for SC829U, 219U (X11 24DIMM, right side)
Riser Card	RSC-R1UW-E8R	1	1U RHS WIO Riser card with one PCI-E x8 slot
Riser Card	RSC-R2UW-4E8	1	2U LHS WIO Riser card with four PCI-E x8 slots
Heatsink / Retention	SNK-P0068PS	2	2U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
Power Supply	PWS-1K02A-1R	2	1U 1000W Redundant Power Supply 73.5mm width Titanium Level,RoHS/REACH
FAN 1	FAN-0118L4	4	80 x 80 x 38 mm, 9.5K RPM, 4-pin PWM Fan, Hot

Optional Parts List

	Part Number	Qty	Description
Add-on card for internal M.2 NVMe	AOC-SLG3-2M2	1	Low Profile PCI-E x8 add-on card supports 2 PCI-E 3.0 x4 M-Key M.2 NVMe Modules
2U Cable Management Arm	MCP-290-00128-0N & MCP-290-00127-0N	1	2U Supermicro Cable Management Arm 2nd Gen (Compatible for racks that are 42" in depth)
Internal Drive Tray for Two 2.5" Drives	MCP-120-82916-0N	1	Internal drive plate Supports Two 2.5" Drive, PCI slots
	CBL-PWEX-0650	1	Power cable for Two internal 2.5" drives
	CBL-0080L	2	
	CBL-0484L Or	2	SATA3 S-S Cable
	CBL-SAST-0654 Or	1	miniSAS(iPass) to 4 SATA Cable
	CBL-SAST-0948	1	miniSAS HD to 4 SATA Cable
Cable for 4 NVMe Hybrid Drive Bays	2 CBL-SAST-0929 & 2 CBL-SAST-0972	1	OCuLink source to MiniSAS HD target V.91,INT,PCIe NVMe SSD, 57CM,34AWG
2.5" NVMe Drive Trays	MCP-220-00167-0B	1~4	Tool-less black hot-swap 2.5" NVMe drive tray (Orange tab, w/ key lock, clip design)
	MCP-220-00127-0B		Black hot-swap 2.5" NVMe drive tray (Orange tab, w/ key lock)
2 Internal M.2 slots (1 SATA, 1 NVMe)	RSC-UMR-8 & CBL-SAST-0538 & MCP-120-82924-0N & MCP-310-21902-0N	1	1U Ultra RHS Riser Card with 1 PCIE/SATA Hybrid M.2 & 1 PCIE X8
2 Rear 2.5" Hot-swap SATA Drive Bays (Complete System Only)	MCP-240-82922-0N-OEM	-	Rear 2x 2.5" HDDs riser bracket kit for SC829U/219U, tool-less
Storage Control Card and Cable(s)	AOC-S3008L-L8e	1	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 122HDD, HBA
	AOC-S3008L-L8i		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 63HDD, RAID 0,1,1E
	AOC-S3108L-H8iR		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60

Compatible Networking Cables and Transceivers for System default Networking (AOC-2UR68-m2TS)	-	1~2	Networking Cables and Transceivers Compatibility Matrix
Network Card(s)	AOC-SGP-i2/4 AOC-STGN-i1S/i2S AOC-STGF-i2S AOC-STG-i4S AOC-STG-b4S AOC-STG-i2T AOC-STGS-i1/2T AOC-STG-i4T AOC-STG-i2 AOC-S25G-m2S AOC-S40G-i2Q More	- - - - - - - - - - - -	Standard LP, 2/4x GbE RJ45, PCI-E x4, Intel i350 Standard LP, 1/2x 10GbE SFP+, PCI-E x8, Intel 82599EN Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel XL710-BM2 Standard LP, 4x 10GbE SFP+, PCI-E x8, Intel XL710 Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X540 Standard LP, 1/2x 10GbE RJ45, PCI-E x8, Intel X550 Standard LP, 4x 10GbE RJ45, PCI-E x8, Intel XL710 Standard LP, 2x 10GbE CX4, PCI-E x8, Intel 82598EB Standard LP, 2x 25GbE SFP28, Mellanox ConnectX-4 LX EN Standard LP 2-port 40GbE controller, Intel Fortville XL710 AOC Compatibility Matrix
CacheVault(s)	BTR-CV3108-U1	-	CacheVault for Broadcom 3108 with Supercap mounting for 2U Ultra
TPM security module	AOM-TPM-9670H-S AOM-TPM-9671H-S	1 1	TCG 2.0 compliant trusted platform module (TPM), Horizontal FF TCG 1.2 compliant trusted platform module (TPM), Horizontal FF
Intel VROC RAID Key	AOC-VROCINTMOD AOC-VROCSTNMOD AOC-VROCPREMOD	1 1 1	Intel VROC, RAID 0, 1, 5, 10 (Intel SSD Only) Intel VROC Standard, RAID 0, 1, 10 Intel VROC Premium, RAID 0, 1, 5, 10
Global Services & Support	OS4HR3/2/1 OSNBD3/2/1	- -	3/2/1-year onsite 24x7x4 service 3/2/1-year onsite NBD service
Software	SFT-OOB-LIC • eStore	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)