



Feature

- * 1U cabinet design, small in size and light in weight.
- * Adopt the latest class D digital amplifier design, with low distortion and high efficiency.
- * Adopt switched power supply technology, with high efficiency, to effectively suppress the harmonics of the power supply, meeting the EU green power supply standard.
- * Adopt smart peak clipper to control the power module and speaker system to work in a safe range.
- * Designed with standard XLR input interface and LINK output interface, convenient for different user needs.
- * Support soft start to prevent absorbing large current from the power grid during startup and interfering with other electrical equipment.
- * Smart control forced heat dissipation design, low fan noise and high heat dissipation efficiency.
- * Support three optional modes: mono, stereo, bridge.
- * Support overvoltage protection, undervoltage protection, overcurrent protection, DC protection, output short circuit protection, temperature control fan and so on.

Specification

Model	TC-2350B
Output power	Stereo@8Ω: 350W×2 ; Stereo@4Ω: 600W×2
Input sensitivity	2.2dBu(1V)
Input impedance	10KΩ
Frequency response (@1W Power)	20Hz-20KHz/±1dB @8Ω
THD+N (@1/8 power)	≤0.01%
Isolation (@1KHz)	≥80dB
Damping coefficient(@1KHz)	≥200@ 8 ohms
SNR (A-weighted)	≥93dB
Input voltage	~220V/50Hz
Maximum power consumption	850W
Dimension (L*W*H)	484*206*44
Weight	3.8kg