

Hyper SuperServer SYS-222H-TN (Complete System Only) **New**

Datasheet Share

2U Hyper with 8 hot-swap 2.5" NVMe/SAS/SATA bays and 4 PCIe 5.0 x16 slots + up to 2 PCIe 5.0 x16 AIOM slots



Key Applications

- Virtualization
- High Performance Computing
- Enterprise Server
- Software-defined Storage
- Cloud Computing

Key Features

- Dual Intel® Xeon® 6 6700 series processors with E-cores
- 32 DIMM slots supporting up to 4TB of memory
- Optional PCIe slot configurations up to 8 PCIe 5.0 x8 or 4 PCIe 5.0 x16 slots with support for double-width GPU/Accelerator cards
- Flexible networking options with up to 2 AIOM networking slots (OCP NIC 3.0 compatible)

[Get Pricing](#)

[Contact Us](#)

Specifications Resources & Downloads Parts List

Product SKUs

SuperServer **SYS-222H-TN**

Motherboard

Super X14DBM-SP

Processor

CPU Dual Socket E2 (LGA-4710)
[Intel® Xeon® 6700 series processors with E-cores](#)

Core Count Up to 144C/144T; Up to 108MB Cache per CPU

Note Supports up to 330W TDP CPUs (Air Cooled)
Supports up to 330W TDP CPUs (Liquid Cooled)

GPU

Max GPU Count Up to 4 double-width or 8 single-width GPUs

System Memory

Memory Slot Count: 32 DIMM slots
Max Memory (1DPC): Up to 2TB 6400MT/s ECC DDR5 RDIMM
Max Memory (2DPC): Up to 4TB 5200MT/s ECC DDR5 RDIMM
[View Memory Options >](#)

On-Board Devices

NVMe NVMe; RAID 0/1/5/10 support (Intel® VROC RAID key required)
[View NVMe Options >](#)

Chipset System on Chip

Network Connectivity Via AIOM
[View AIOM Options >](#)
[View AOC Options >](#)

Input / Output

LAN 1 RJ45 1 GbE Dedicated BMC LAN port

USB 2 USB 3.0 ports(rear)
2 USB 3.0 ports(Header)

Video 1 VGA port

System BIOS

BIOS Type AMI 64MB SPI Flash

Management

Software [SuperCloud Composer](#)
[Supermicro Server Manager \(SSM\)](#)
[Super Diagnostics Offline \(SDO\)](#)
[Supermicro Thin-Agent Service \(TAS\)](#)
[SuperServer Automation Assistant \(SAA\) New!](#)

Power configurations Power-on mode for AC power recovery
ACPI Power Management

Security

Hardware Trusted Platform Module (TPM) 2.0
Silicon Root of Trust (RoT) – NIST 800-193 Compliant

Features Cryptographically Signed Firmware
Secure Boot
Secure Firmware Updates
Automatic Firmware Recovery
Supply Chain Security: Remote Attestation
Runtime BMC Protections
System Lockdown

PC Health Monitoring

CPU Monitors for CPU Cores, Chipset Voltages, Memory

FAN Fans with tachometer monitoring
Status monitor for speed control
Pulse Width Modulated (PWM) fan connectors

Temperature Monitoring for CPU and chassis environment
Thermal Control for fan connectors

Chassis

Form Factor 2U Rackmount

Model **CSE-HS219-R000NP**

Dimensions and Weight

Height 3.5" (88 mm)

Width 17.3" (438.4 mm)

Depth 29.73" (755.2 mm)

Package 10.12" (H) x 23.82" (W) x 37.28" (D)

Weight Gross Weight: 66 lbs (30 kg)
Net Weight: 40 lbs (18.2 kg)

Available Color Silver

Front Panel

LED HDD activity
LAN1 activity
LAN2 activity
Power Fail
Power status
System information (overheat/UID)

Buttons Power On/Off
UID button

Expansion Slots

PCI-Express (PCIe) Configuration Option A*
4 PCIe 5.0 x16 FH/10.5"L double-width slots
1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)
1 PCIe 5.0 x8 AIOM slot (OCP 3.0 compatible)
Option B*
8 PCIe 5.0 x8 (in x16) FH/10.5"L slots
1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)
1 PCIe 5.0 x8 AIOM slot (OCP 3.0 compatible)
(*Requires additional parts, please see the optional parts list for details. For more details on PCIe slot configuration options, please refer to the system callout images above.)
[View AOC Options >](#)

CXL Support Up to 4 CXL 2.0 x16/x8 devices

Drive Bays / Storage

Drive Bays Configuration Default: Total 8 bays
8 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays
Option A: Total 16 bays
16 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays
Option B: Total 24 bays
24 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays
(*NVMe/SAS/SATA support may require additional storage controller and/or cables, please see the optional parts list for details)
[View NVMe Options >](#)
[View Drive Options >](#)

M.2 2 M.2 PCIe 5.0 x2 NVMe slots (M-key 2280/22110)
[View M.2 Options >](#)

System Cooling

Fans 4x 8cm heavy duty fans with optimal fan speed control

Air Shroud 2 Air Shrouds

Liquid Cooling Direct to Chip (D2C) Cold Plate (optional)

Power Supply

2X 1200W 2X 2000W 2X 1600W 2X 2 >

2x 1200W Redundant (1 + 1) Titanium Level (96%) power supplies

Dimension (WxHxL) 73.5 x 40 x 265 mm

Input 800W: 100-127Vac
800W: 100-127Vac / 50-60Hz
1200W: 200-240Vac
1200W: 200-240Vac / 50-60Hz
1200W: 230-240Vdc / 50-60Hz (for CCC only)

+12V Max: 66.7A / Min: 0A (100Vac-127Vac)
Max: 83A / Min: 0A (100Vac-127Vac)
Max: 100A / Min: 0A (200Vac-240Vac)
Max: 100A / Min: 0A (230Vdc-240Vdc) (for CCC only)

12V SB Max: 2.1A / Min: 0A

Output Type Backplanes (gold finger)

Operating Environment

Environmental Spec. Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F)
Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)
Operating Relative Humidity: 8% to 90% (non-condensing)
Non-operating Relative Humidity: 5% to 95% (non-condensing)

Certain products may not be available in your region

Global SKU English

About Us

- Company Profile
- Green Computing
- Investor Relations
- Careers
- Site Map
- Glossary

News

- Press Releases
- Supermicro in the News
- Product Reviews
- Events
- Webinars

Resources

- Product Briefs
- Solution Briefs
- Success Stories
- Videos
- White Papers
- Thought Leadership
- MySupermicro
- Data Center Stories

Connect & Follow

- Locations
- Contact Us
- Newsletter Sign-up

