

A+ Server 4023S-TRT



Integrated Board



H11DSi-NT

Views: | [Angled View](#) | [Side View](#) | [Front View](#) | [Rear View](#) |

[▶ Drivers & Utilities](#) | [▶ BIOS](#) | [▶ IPMI](#) | [▶ Tested Memory](#) | [▶ Tested M.2 List](#) | [▶ NVMe Options](#) | [▶ Tested AOC](#) | [▶ Manuals](#) | [▶ OS Certification Matrix](#) | [▶ Compatible GPU List](#) | [▶ Quick-References Guide](#) | [▶ Drive Options](#)

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Key Features

Cloud Computing

Data Center

General purpose, SMB, Web Hosting

1. Dual AMD EPYC™ 7001/7002* Series Processors (*AMD EPYC 7002 series drop-in support requires board revision 2.x)
2. 2TB Registered ECC DDR4 2666MHz SDRAM in 16 DIMMs (7001 Processors)
4TB Registered ECC DDR4 3200MHz SDRAM in 16 DIMMs (Board revision 2.x required + 7002 Processors)
3. Expansion slots:
2 PCI-E x16 slots
3 PCI-E x8 slots
M.2 Interface: 1 SATA/PCI-E 3.0 x2 (Platform with EPYC 7002 processor only supports PCI-E type M.2 module)
M.2 Form Factor: 2280, 22110
M.2 Key: M-key
4. Integrated IPMI 2.0 + KVM with dedicated LAN
• **Software Out of Band License key (SFT-OOB-LIC) included for OOB BIOS management**
5. Dual 10G LAN ports
6. 8 hot-swap 3.5" SATA3 drive bays;
3 peripheral 5.25" drive bays;
1 M.2 NVMe SSD supported
7. 1280W Redundant Power Supplies
Platinum Level
(Full redundancy based on configuration and application load)



Specifications

Product SKUs

AS -4023S-TRT ■ A+ Server 4023S-TRT

Motherboard

H11DSi-NT

Processor/Chipset

CPU ■ Dual AMD EPYC™ 7001/7002* series Processors (* Board revision 2.x required)
 ■ Socket SP3
 ■ Supports CPU TDP 225W / cTDP up to 240W*

Cores ■ Up to 32 Cores (Board revision 1.x + 7001 Processors)
 ■ Up to 64 Cores (Board revision 2.x + 7002 Processors)

Chipset ■ System on Chip (SoC)

System Memory

Memory Capacity ■ 16 DIMM slots
 ■ Supports up to 2TB Registered ECC DDR4 2666MHz SDRAM (7001 Processors)
 ■ Supports up to 4TB Registered ECC DDR4 3200MHz SDRAM (Board revision 2.x required + 7002 Processors)
 ■ 8-channel memory bus

Memory Type ■ DDR4 2666 MHz Registered ECC, 288-pin gold-plated DIMMs (7001 Processors)
 ■ DDR4 3200 MHz Registered ECC, 288-pin gold-plated DIMMs (Board revision 2.x required + 7002 Processors)

DIMM Sizes ■ 4GB, 8GB, 16GB, 32GB, 64GB, 128GB, 256GB* (* Board revision 2.x required + 7002 Processors)

Memory Voltage ■ 1.2V

Error Detection ■ Corrects single-bit errors
 ■ Detects double-bit errors (using ECC memory)

On-Board Devices

SATA ■ SATA3 (6 Gbps)

IPMI ■ Support for Intelligent Platform Management Interface v.2.0
 ■ IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
 ■ ASPEED AST2500 BMC

Network Controllers ■ 2 Intel® X550 10GBase-T Ethernet Controllers
 ■ 1 Realtek RTL8211E PHY (dedicated IPMI)

VGA ■ ASPEED AST2500 BMC

Expansion Slots

PCI-Express ■ 2 PCI-E x16 slots
 ■ 3 PCI-E x8 slots

Chassis

Form Factor ■ Tower / 4U Rackmountable

Model ■ CSE-745BTS-R1K28BP2

Dimensions and Weight

Height ■ 17.8" (452mm)

Width ■ 7" (178mm)

Depth ■ 25.5" (647mm)

Package ■ 24.6" (H) x 14" (W) x 31.3" (D)

Weight ■ Net Weight: 59 lbs (26.76 kg)
 ■ Gross Weight: 62 lbs (28.12 kg)

Front Panel

Buttons ■ Power On/Off button
 ■ System Reset button

LEDs ■ Power LED
 ■ Hard drive activity LED
 ■ 2x Network activity LEDs
 ■ System Overheat LED / Fan fail LED / UID LED

Drive Bays

Hot-swap ■ 8 hot-swap 3.5" Drive Bays:
 ■ 8 SATA3 by default
 ■ or 8 SAS3

Peripheral Drives

5.25" ■ 3 peripheral 5.25" drive bays

Backplane

HDD Backplane ■ Supports 8 SATA3 or 8 SAS3 HDD

System Cooling

Fans ■ 3 internal hot-swap 9400 RPM fans
 ■ 2 external rear hot-swap 9400 RPM fans

Power Supply

1280W Redundant High-efficiency Digital Power Supplies w/ PMBus 1.2

AC Input ■ 1000W Output @ 100-140V, 8-12A, 50-60Hz
 ■ 1280W Output @ 180-240V, 6-8A, 50-60Hz

DC Output ■ 1000W: +12V/83A; +5Vsb/4A
 ■ 1280W: +12V/106.7A, +5Vsb/4A

Certification



Platinum Certified
 [[Test Report](#)]

PC Health Monitoring

CPU ■ Monitors CPU Core Voltages, +12V, +3.3V, +5V, +5V standby, 3.3V standby, VBAT
 ■ CPU switching voltage regulator

M.2	<ul style="list-style-type: none"> Interface: 1 SATA/PCI-E 3.0 x2 (Platform with EPYC 7002 processor only supports PCI-E type M.2 module) Form factor: 2280, 22110 Key: M-key
------------	--

Input / Output

SATA	<ul style="list-style-type: none"> 10 SATA3 (6 Gbps) ports
LAN	<ul style="list-style-type: none"> Dual 10G LAN ports 1 RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 2 USB 3.0 ports (rear) 2 USB 2.0 ports (rear)
VGA	<ul style="list-style-type: none"> 1 VGA port
SAS	<ul style="list-style-type: none"> 8 SAS3 ports support via optional Add-on Card
NVMe	<ul style="list-style-type: none"> 2 NVMe support with optional cables
Others	<ul style="list-style-type: none"> 1 COM port (rear) 2 SATA DOM power connector TPM 1.2 header

System BIOS

BIOS Type	<ul style="list-style-type: none"> AMI 128Mb SPI Flash EEPROM
BIOS Features	<ul style="list-style-type: none"> Plug and Play (PnP) DMI 2.3 PCI 2.2 ACPI 5.1 USB Keyboard Support SMBIOS 3.1.1

FAN	<ul style="list-style-type: none"> Up to 8-fan status tachometer monitoring Up to eight 4-pin fan headers Status monitor for speed control Pulse Width Modulated (PWM) fan connectors
------------	---

Temperature	<ul style="list-style-type: none"> Monitoring for CPU and chassis environment CPU Thermal Trip Support Thermal control for 8x Fan connectors I²C Temperature Sensing Logic
--------------------	---

LED	<ul style="list-style-type: none"> CPU / System Overheat LED
------------	---

Other Features	<ul style="list-style-type: none"> Chassis Intrusion Detection Chassis Intrusion Header
-----------------------	---

Operating Environment / Compliance

RoHS	<ul style="list-style-type: none"> RoHS Compliant
-------------	--

Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
----------------------------	---

Список деталей

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard	MBD-H11DSi-NT	1	Super H11DSi-NT Motherboard
Chassis	CSE-745BAC-R1K28BP2	1	4U Chassis
Backplane	BPN-SAS3-743A-N4	1	8-port 4U/Tower (SC743/745) 3.5-inch SAS3/SAS2/SATA3 12Gbps backplane, 4 of 8 ports support NVMe devices
Cable	CBL-SAST-0508-01	2	Internal Mini-SAS to Mini-SAS HD 50cm w/ SB, 30AWG,HF,RoHS/REACH,PBF
Heat Sink	SNK-P0063P	2	2U Passive CPU Heat Sink for AMD Socket SP3 Processors
IO Shield	MCP-260-00042-0N	1	STD I/O shield for X9 socket R server MB with Gasket.
Power Supply	PWS-1K28P-SQ	2	1U 1280W, redundant single output power supply
Software	<u>SFT-OOB-LIC</u>	1	OOB Management Package (per node license)

Optional Parts List

	Part Number	Qty	Description
NVMe support kit	MCP-220-00080-0B	-	3.5" to 2.5" HDD tray - ADD QTY 1 per drive (Hot swap not supported)
	CBL-SAST-0818	-	OCuLink v.91,INT,PCIe NVMe SSD, 55CM - ADD QTY 1 per drive
DVD Drive Kit	DVM-LITE-DVDRW24-HBT	-	BLACK LITE-ON 5.25" HH 24X DVD-RW SATA DRIVE PBF
	1x CBL-SAST-0624	-	SATA,INT,ROUND,ST-ST,70CM,30AWG
	1x CBL-0082L	-	Y split, big 4 pin to two RA SATA power extension 15cm, 18AWG
Mounting Rails	CSE-PT26L-B	-	4U Chassis Rail Kits SC743,745 (w/ 2pcs Black Chassis Ears)
Tray	MCP-220-00044-0N	-	Dual 2.5" fixed HDD bracket for SC502, 503, 510, 512, 515U
3.5" to 2.5" HDD tray Converter	MCP-220-00080-0B	-	Black hot-swap gen 2 3.5" to 2.5" HDD tray – ADD QTY 1 per drive
Storage Control Card and Cable(s)	AOC-S3008L-L8e	-	Std LP, 8 WIO L ports, 12Gb/s per port- Gen3, 122HDD, HBA
	2x CBL-SAST-0593	-	Internal Mini-SAS HD to Mini-SAS HD 60cm,30AWG,12Gb/s
	AOC-S3008L-L8i	-	Std LP, 8 WIO L ports, 12Gb/s per port- Gen3, 63HDD, RAID 0,1,1E
	2x CBL-SAST-0593	-	Internal Mini-SAS HD to Mini-SAS HD 60cm,30AWG,12Gb/s
	AOC-S3108L-H8iR	-	Std LP, 8 WIO L ports, 12Gb/s per port- Gen3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60
	2x CBL-SAST-0593	-	Internal Mini-SAS HD to Mini-SAS HD 60cm,30AWG,12Gb/s
TPM	AOM-TPM-9665V	-	Vertical TPM with Infineon 9665 TCG 1.2
	AOM-TPM-9665V	-	AOM-TPM-9665V using SLB9665 Chipset supporting TPM2.0,RoHS/REACH
Global Services & Support	<u>OS4HR3/2/1</u>	-	3/2/1-year onsite 24x7x4 service
	<u>OSNBD3/2/1</u>	-	3/2/1-year onsite NBD service
Software	<u>SFT-DCMS-Single</u>	1	DataCenter Management Package (per node license)