

# DH-SD50225DB-HC

2MP 25x Starlight HDCVI PTZ Camera



- 1/2.8" 2Megapixel STARVIS™ CMOS.
- Powerful 25x optical zoom.
- Starlight technology.
- 120 dB true WDR, 3D NR.
- Max. 25/30 fps@1080p, 25/30/50/60 fps@720p.
- IK10.
- IP67.



## System Overview

With its powerful optical zoom, and accurate pan and tilt capabilities, the HDCVI PTZ camera series provides an all-in-one solution for large-scale monitoring. It harnesses the latest starlight technology, allowing it to produce highly detailed images even in low light conditions. These cameras offer smooth control and high-grade protection that enable them to meet the requirements of video surveillance in small and medium-sized scenes.

## Functions

### Starlight Technology

With advanced image processing technology and optical technology, Dahua Starlight technology can provide clear colorful video in the environment of low illuminance. It widely applies to various environments of low illuminance.

### 3DNR

Dahua's 3DNR technology reduces image noise with little to no impact on image sharpness, especially in poor lighting conditions. It detects the noise, and compares the sequential frames to effectively reduce the noise. It also makes efficient use of bandwidth, saving on storage space.

### Long Distance Transmission

HDCVI technology provides long distance transmission in real time without transmission loss. It supports transmission distances up to 300m for 2MP HD videos through coaxial cables, and up to 200m through UTP cables.

\*The results were obtained and verified through rigorous testing in Dahua's test laboratory.

### 3 Signals over 1 Coaxial Cable

HDCVI technology supports 3 signals (video, audio\* and data) which are simultaneously transmitted over a coaxial cable. Dual-way data transmission allows the HDCVI camera to interact with the XVR to perform various actions such as sending control signals and triggering alarms.

\* Audio input is available for select HDCVI camera models.

### Wide Dynamic Range

The camera produces vivid images, even in high-contrast lighting conditions, by using industry-leading wide dynamic range (WDR) technology. For scenes that quickly alternate between bright and low lighting, WDR adjusts to fully capture both the bright and dark areas of a scene, producing superior quality videos.

### PFA Technology

PFA technology has introduced new methods of judgment that ensure the accuracy and predictability of the direction of subject distance adjustment. The result is a set of advanced focusing algorithms that ensure image clarity when zooming and that shorten focus time. This makes the camera highly advanced in its functions, substantially improving the quality of your experience.

### Protection (IP67, TVS 6000 V)

IP67, TVS 6000 V lightning proof, surge protection, and voltage transient protection.

**Technical Specification**

Camera

|                          |  |
|--------------------------|--|
| Image Sensor             | 1/2.8" CMOS  |
| Pixel                    | 2 MP   |
| Max. Resolution          | 1920 (H) × 1080 (V)  |
| ROM                      | 128 MB   |
| RAM                      | 256 MB   |
| Electronic Shutter Speed | 1/3 s–1/30,000 s   |
| Scanning System          | Progressive  |
| Min. Illumination        | 0.005 lux@F1.6 (Color, 30 IRE);<br>0.0005 lux@F1.6 (B/W, 30 IRE) |

Lens

|                      |  |
|----------------------|--|
| Focal Length         | 4.8 mm–120 mm  |
| Max. Aperture        | F1.6–F3.5  |
| Field of View        | H: 59.7°–3.5°;<br>V: 34.1°–2.0°;<br>D: 68.6°–4.0°  |
| Optical Zoom         | 25×  |
| Focus Control        | Auto; semi-auto; manual  |
| Close Focus Distance | 0.1 m–2 m (0.33 ft–6.56 ft)  |
| Iris Control         | Auto; manual   |
| DORI Distance        | Detect      Observe      Recognize      Identify   |
|                      | 1655.2 m (5430.45 ft)      653.8 m (2145.01 ft)      331.0 m (1085.96 ft)      165.5 m (542.98 ft) |

PTZ

|                      |  |
|----------------------|--|
| Pan/Tilt Range       | Pan: 0° to 360° endless;<br>Tilt: 0° to +90°, auto flip 180° |
| Manual Control Speed | Pan: 0.1°–350°/s<br>Tilt: 0.1°–250°/s                        |
| Preset Speed         | Pan: 500°/s;<br>Tilt: 500°/s                                 |
| Preset               | 300  |
| Tour                 | 8 (up to 32 presets per tour)                                |
| Pattern              | 5  |
| Scan                 | 5  |
| Power-off Memory     | Yes  |
| Idle Motion          | Pattern;Preset;Scan;Tour                                     |
| PTZ Protocol         | DH-SD<br>Pelco-P/D (Auto recognition)                        |

Video

|                  |  |
|------------------|--|
| Resolution       | 1080p (1920 × 1080); 720p (1280 × 720); D1 (704 × 576/704 × 480) |
| Video Frame Rate | 1080p (25/30 fps); 720p (25/30/50/60 fps)                        |
| Day/Night        | Yes  |

|                 |  |
|-----------------|--|
| BLC             | Yes  |
| WDR             | 120dB  |
| HLC             | Yes  |
| White Balance   | Auto; indoor; outdoor; tracking; manual; sodium lamp; natural light; street lamp |
| Gain Control    | Auto; manual   |
| Noise Reduction | 2D NR; 3D NR   |
| Defog           | Electronic   |
| Digital Zoom    | 16×  |
| Image Rotation  | 180°   |
| Privacy Masking | Yes  |
| S/N Ratio       | ≥50 dB   |

Function

|                         |   |
|-------------------------|---|
| CVI Product Output Mode | TVI;CVI;CVBS;AHD(CVBS is only used for debugging) |
|-------------------------|---|

Certification

|                |  |
|----------------|--|
| Certifications | CE: EN55032/EN55024/EN50130-4<br>FCC: Part15 subpart B, ANSI C63.4-2014<br>UL: UL60950-1+CAN/CSA C22.2, No.60950-1 |
|----------------|--|

Port

|               |   |
|---------------|---|
| Analog Output | 1 channel (CVBS/CVI output, BNC)                  |
| RS-485        | 1 (baud rate range: 1200 bps–9600 bps)            |
| Audio Input   | 1 channel (LINE IN, bare wire)                    |
| Alarm Linkage | Scan; preset; tour; pattern; alarm digital output |
| Alarm Event   | Alarm input                                       |

Power

|                   |                                   |
|-------------------|-----------------------------------|
| Power Supply      | 24 VDC, 2.5 A ± 25%               |
| Power Consumption | Basic: 10.5 W<br>Max.: 14 W (PTZ) |

Environment









|                       |   |
|-----------------------|---|
| Operating Temperature | –40 °C to +60 °C (–40 °F to +140 °F)  |
| Operating Humidity    | ≤95%  |
| Protection            | IP67; IK10; TVS 6000V lightning proof; surge protection; voltage transient protection |

Structure

|                    |                                       |
|--------------------|---------------------------------------|
| Product Dimensions | 253.0 mm × Φ186.2 mm (9.96" × Φ7.33") |
| Net Weight         | 2.5 kg (5.51 lb)                      |
| Gross Weight       | 4.4 kg (9.70 lb)                      |

**Ordering Information**

| Type             | Model               | Description                              |
|------------------|---------------------|--|
| 2MP HDCVI Camera | DH-SD50225DB-HC     | 2MP 25x Starlight PTZ HDCVI Camera, PAL  |
|                  | DH-SD50225DBN-HC    | 2MP 25x Starlight PTZ HDCVI Camera, NTSC |
|                  | SD50225DB-HC        | 2MP 25x Starlight PTZ HDCVI Camera, PAL  |
|                  | SD50225DBN-HC       | 2MP 25x Starlight PTZ HDCVI Camera, NTSC |
| Accessories      | DC24V/2.5A          | Power Adapter                            |
|                  | PFA110              | Mount Adapter                            |
|                  | PFB300S             | Wall Mount Bracket                       |
|                  | PFA120              | Junction Box                             |
|                  | PFB300C             | Ceiling Mount Bracket                    |
|                  | PFB301C             | Ceiling Mount Bracket                    |
|                  | PFA150              | Pole Mount Bracket                       |
|                  | PFA151              | Corner Mount Bracket                     |
|                  | PFB303S             | Parapet Mount Bracket                    |
| PFB301S-E        | Plane Mount Bracket |  |

| Wall Mount   | Ceiling Mount   | Ceiling Mount   |
|--|---|---|
| PFA110+PFB300S+PFA120  | PFA110+PFB300C  | PFA110+PFB301C  |
|  |  |  |
| Pole Mount(Vertical)   | Pole Mount(Horizontal)  | Corner Mount  |
| PFA110+PFB300S+PFA150  | PFA110+PFB300C+PFA150   | PFA110+PFB300S+PFA151   |
|   |  |  |
| Plane Mount  | Parapet Mount   |   |
| PFB301S-E  | PFA110+PFB303S  |   |
|  |  |   |

**Accessories**

Included:



DC24V/2.5A Power Adapter



PFA110 Mount Adapter



PFB300S Wall Mount Bracket

Optional:



PFA120 Junction Box



PFB300C Ceiling Mount Bracket



PFB301C Ceiling Mount Bracket



PFA150 Pole Mount Bracket



PFA151 Corner Mount Bracket



PFB303S Parapet Mount Bracket



PFB301S-E Plane Mount Bracket

**Dimensions (mm [inch])**

