



Description

*The product use intelligent control technology, take intelligent terminal as application concept, adopt original guide rail design, one key operation can automatically complete starting, LCD screen up, elevation and other actions, beautiful desktop, space-saving as the purpose, easy to use. With anti-theft, anti-dust, beautify desktop and other function. Can be widely used in conference, office hotel, teaching studio and other occasion, to meet the customer systems development diversity, and office automation environment demand. It is one ideal assistant of your office and teaching.

Feature

- *No exposed cable, no connection backboard, no exposed screws, ensure a nice overall appearance of touch display screen.
- *Adopt fully aluminum structure, high-quality aluminum and CNC processing. The aluminum-alloy structure and case make the equipment more exquisite, handiness and elegant.
- *Equipment surface treatment is anodized, bright color.
- *Equipment panel thickness of only 3mm, width of only 70mm, small footprint.

- *Adopt imported steel wire, cooperated with high precision guide rail and linear bearing, AC geared motor as driving force, reduce noise to minimum.
- *17.3-inch ultra-thin LCD touch screen display, resolution up to 1920*1080P, clear and bright display, adjustable backlight design, to prevent fatigue caused by too bright or too dark.
- *Support HDMI and VGA two channel signal input, when there is only one signal input, the screen will automatically recognize this signal, when these two signal input at the same time, can be manually switched from panel key, when no signal input, the screen will automatically enter into power saving mode.
- *The device can be centrally controlled through central control software, can be controlled by the host computer, one key can make all device in the room go up or down.
- *Built-in loop-through output power outlet, can power supply to the terminal to reduce terminal power outlet wiring, make project site wiring more neat and beautiful.
- *With USB port on the desktop panel, the user can read the file in the USB or upload files to the USB.

Model	TS-F173T
Touch Screen	Support
Lifting Time	28S
Elevation Angle	0-30°
Case Size	462*60*518mm
Panel Size	476*70*3mm
The Lifting Hole Size	434.5*21.5mm
Desk Cut-Out Size	463*62mm
Panel Chimtay Size	477*71*3mm
Working Environment	-20°C ~ 50°C, relative humidity≤70%
Screen Size	17.3"
Screen Aspect Ratio	16 : 9
Resolution	1920*1080
Video Port	VGA、HDMI
Video Switching	VGA、HDMI(manually signal switching by buttons)
Backlight Type	WLED, 15K hour, with LED driver
Contrast	700: 1
Brightness	300cd/m²
Viewing Angle	89/89/89/89(Typ)
Screen Thickness	10mm
Signal System	EDP
Power Consumption	>18W
Power Supply	AC 220V 50-60/HZ
Weight	8.5Kg