



# Portable Active Column Speaker

## KS-12A35W



### Description

It is used in mobile performances, small and medium clubs, auditoriums, banquet halls, multipurpose halls and various high-end occasions.

### Feature

- \* Adopt one 12-inch woofer and eight 3.5-inch mid tweeters.
- \* The woofer is made of 15mm birch plywood; the column speaker is made of 9mm birch plywood; the surface is sand-sprayed, wear-resistant and high-grade.
- \* Active portable linear array speaker system contains powerful sound effect, portability, easy installation, high sound pressure level and a wide low frequency range.
- \* The integrated woofer adopts a band-pass dual inverted design to provide the powerful bass effect; the mid tweeter adopts a phase plug line sound source design, while avoiding the bulky shape.
- \* Built in amplifier class D.
- \* 2-band EQ.
- \* Number of Mixer Channels  $\geq 3$ .
- \* Volume control, Power indicator, ON/OFF switch.
- \* Protection heating, over current, short circuit.



# Portable Active Column Speaker

## KS-12A35W

### Specification

<b>Model</b>	KS-12A35W
<b>Rated power</b>	600W+600W
<b>Peak power</b>	24 00W+ 24 00W
<b>Crossover frequency</b>	4th/200Hz, DSP electronic frequency division
<b>Frequency range</b>	40Hz-20KHz
<b>Input</b>	2 XLR multi-function jack inputs, 1 stereo RCA input, 1 Bluetooth input, 2x XLR phantom power, AUX, Bluetooth (USB option)
<b>Output</b>	1*Line out, 1 XLR output
<b>Function</b>	Support low frequency boost, Bluetooth support TWS, support one-key noise reduction
<b>Maximum SPL (rated/peak)</b>	122dB/128dB
<b>Voltage input</b>	AC 220V 50Hz-60Hz
<b>Coverage</b>	140° (H) 40° (V)
<b>Woofers</b>	12" × 1
<b>Mid tweeter</b>	3.5" × 8
<b>Indicators</b>	Mixer on, battery status, charge
<b>THD</b>	<= 0.05%
<b>Mid tweeter</b>	3.5" × 8
<b>Net weight</b>	25.5kg
<b>Dimension (H×W×D)</b>	Woofers: 625×365×450mm ; Column speaker: 800×103×180mm ; Support rod: 800×35×50mm
<b>Total height</b>	2000mm